Form 9-331 (May 1963)	DEPARTMENT OF THE INTERIOR (Other Instructions on Telephone) GEOLOGICAL SURVEY			Form approved. Budget Bureau No. 42-R1424. 5. LEASE DESIGNATION AND SERIAL NO. Jicarilla Apache Cont. 34 6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
(Do not	SUNDRY NOTICE tuse this form for proposal Use "APPLICAT	7. UNIT AGREEMENT NAM	ME -			
OIL X GAS WELL OTHER 2. NAME OF OPERATOR Skelly Oil Company					8. FARM OR LEASE NAME Jicarilla "C"	
3. ADDRESS OF OPERATOR 1860 Lincoln Street, Denver, Colorado 80203 4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface					9. WELL NO. 20 10. FIELD AND POOL, OR WILDCAT Otero Gallup 11. SEC., T., R., M., OR BLK. AND	
660' FNL & 660' FWL Section 33-25N-5W					SURVEY OR AREA Section 33-25N-5W 12. COUNTY OR PARISH 13. STATE	
14. PERMIT NO.	•	15. ELEVATIONS (Show 6720 GL	whether DF, RT, Cl		Rio Arriba	New Mexico
16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:						<u></u>
TEST WAT FRACTURE SHOOT OR REPAIR W (Other)	TREAT	ULL OR ALTER CASING ULTIPLE COMPLETE BANDON* HANGE PLANS	<u>x</u>	Completion or Recomp	ALTERING C. ABANDONMEI s of multiple completion letion Report and Log for	on Well

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

The Mesaverde formation was tested w/negative results; therefore, plans are to plug and abandon as follows:

(Present cement behind 5-1/2" casing is from TD to 4906' and 3761-1683' covering the Chacra, Pictured Cliffs and Ojo Alamo formation).

First Plug - Gallup perfs. 6064-6168' w/25 sx of cement filling up to 6000'. Second Plug - In 5-1/2" casing hole at 4400' and in and out of casing 4450-4350'. Pull approximately 1500' of 5-1/2" casing.

Third Plug - Spot 100' plug inside and outside of 5-1/2" casing stub. Fourth Plug - Spot 100' plug from 400-300' across the surface casing shoe.

Fifth Plug - Spot 30' surface plug w/standard dry hole marker.

Heavy mud between all plugs.

		SEP 18 DIZ
SIGNED SIGNED	TITLE Dist. Operations Supt.	DATE Sept. 14, 1972
(This space for Federal or State office (SF) APPROVED BY	TITLE	DATE