

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

Jicarilla Apache Cont. 34

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR
Skelly Oil Company

3. ADDRESS OF OPERATOR
1860 Lincoln Street, Denver, Colorado 80203

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

660' FNL & 660' FWL Section 33-25N-5W

14. PERMIT NO. 6720' GL 6730' DF

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Jicarilla "C"

9. WELL NO.
20

10. FIELD AND POOL, OR WILDCAT
Otero Gallup

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Section 33-25N-5W

12. COUNTY OR PARISH 13. STATE
Rio Arriba New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANS

(Other)

(Other)

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

The Mesaverde formation was tested w/negative results; therefore, plans are to plug and abandon as follows:

(Present cement behind 5-1/2" casing is from TD to 4906' and 3761-1683' covering the Chacra, Pictured Cliffs and Ojo Alamo formation).

First Plug - Gallup perfs. 6064-6168' w/25 sx of cement filling up to 6000'.

Second Plug - In 5-1/2" casing hole at 4400' and in and out of casing 4450-4350'.

Pull approximately 1500' of 5-1/2" casing.

Third Plug - Spot 100' plug inside and outside of 5-1/2" casing stub.

Fourth Plug - Spot 100' plug from 100' to surface casing shoe.

Fifth Plug - Spot 30' surface plug w/standard dry hole marker.

Heavy mud between all plugs.

PLACE 200' PLUG FROM 2650 - 2850' ACROSS PICT. CLIFFS FM. INSIDE 5 1/2" CSG.

PLACE 350' PLUG FROM 2100 - 2450' ACROSS OJO ALAMO FM. INSIDE 5 1/2" CSG.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Dist. Operations Supt.

DATE Sept. 14, 1972

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

COPY TO BE MAINTAINED

