STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is not to be used for reporting packer leskage tests in Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LFAKAGE TEST

	<u>G</u> ∈	etty Oil C	ompany	Lease	Jicaril	La "C"	XVell No.	19	
ocation f Well: 1	UnitI	Sec27_	Twp. 25N	Rge	5W	Cour	nty Rio	Arriba	
	NAME OF RESERVOIR OR POOL				TYPE OF PROD. (Oll of Gas)		METHOD OF PROD. (Flow or Ari. LHI)		
Upper ompletion	Sout	h Blanco	Pictured (Cliffs G	ffs Gas		:	Casing	
Lower empletion	1 6 1 6 1		G	Gas		Flow Tubi			
			PRE-F	LOW SHUT-IN	PRESSURE DAT	`A			
Upper	Hour, date a	pur, date shul-in Length of time shul-in			Si press paig		Stabilized? (Yes or No:		
	Hour, date shut-in		Langth of time s	Length of time shut-in			Stabilized? (Yes or No)		
				FLOW TES	I NO. 1				
nrimenced at (hour, date).≢					Zone producing (Upper or Lower):				
TIME LAPSED TIME (hour, date) SINCE*		PRESSURE Upper Completion Lower Completion		PROD. ZONE		REMARKS			
10 - 1 4	1 – 84	0 Hr.							
10-1	5-34	24 Hr	332	315		Both	Zones .	Shut In	
10-16	5-84	48 Hr	334	319		U	11	H H	
10-17	7-34	72 Hr	33 6	323		11	11	11 11	
LO <u>- 1</u> 6	3-34	96 Hr	337	134		Upper S	.I. Lo	wer Flow 24	
10-19	9-84	120 Hr	338	129		Upper S	.I. Lov	ver Flow 4	
duction	rate du	ring test							
:		BOPI	D based on	B bls	n Hou	rs Gr	ıv	_ GOR	
i:					u (Otifice or Mea				
					RESSURE DATA			The second secon	
pper pletion	our, date shi	ut-ın		Length of time shut-in			Stepifized? (Yes or No)		
Ho	Hour data and la		Length of time shi	Length of time shut-in		St	Stabilized? (Yes or No:		

FLOW TEST NO. 2

Commenced at (hour, da	1te) **			Zone producing (Upp	or Lower):	
TIME (hour, date)	LAPSED TIME SINCE **	PRE Upper Completion	SSURE Lower Completion	PROD. ZONE TEMP.	REMARKS	
. ,						
					Annesse retirem, with states to have regular and a proportion of the state of the s	
			n en		per deservices and a supplier of the	
					COMPONENT COLUMN	
· · · · · · · · · · · · · · · · · · ·						
Production rate d	luring test					
Oil:	ВОР	D based on	Bbls. in	Hours.	Grav GOR	
Gas:		мс	FPD: Tested thru	(Orifice or Meter)		
Remarks:						
I hereby certi v st	nat the informati	on herein contair	red is true and co	mplete to the best	of my knowledge.	
				(2)	etty Oil Company	
Approved New Mexico O	il Conservation I	1 1984 Division	19 C	perator		
Orig	jinal Signed by Ci	ARLES UNILSON	В	y	and O Berhost	
Ву			Т	itleF	ield Technician V	
Title DEPUT	Y OIL & GAS INS	PECTOR, DIST. #3)ate1(0-22-84	

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiple completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion at: shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test'No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 exce.

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midwarpoint) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).