# STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

# **OIL CONSERVATION DIVISION**

Page 1 Revised 10/01/78

This form is not to be used for reporting packer leakage tests

JM J,)		
REMARKS		
•		
√ 24H		
48''		
<del></del>		
_		

## FLOW TEST NO. 2

Commenced at (hout, date) ***					Zone producing (Upper or Lower):			
TIME	LAPSED TIME	PRESSURE Upper Completion Lower Completion		PROD. ZONE		REMARKS		
(hour, date)	BINCETT		<del> </del>	Lower Completion			1885	Transfer of the transfer of
				,	!			
s About 11		. <del>.</del>						
Production rate du	uring test						• • • •	-
Oil:	ВОР	D based on		Bbls. is	n Ho	ours	Grav.	GOR
Gas:	· · · · · · · · · · · · · · · · · · ·		МСБ	PD: Tested thru	(Orifice or M	leter):		**
Remarks:	<del></del>					<u> </u>	<u>.</u>	
						<del></del>		
I hereby certify th	at the informati	on harrin o	ontein 0 8	ed is true and c	omplete to the TE	e best o	of my knowledg	ge.
Approved	l Conservation I	Division		19	Operator Op	er.	for Texas	co Prod Inc.
	linai Signeu by Cl	IARLES GHOL	SON		A1	lan A	A. Kleier	<b>19</b> 44
Ву			PIST				Superinter	ndent
Title	DEPUTY CL & GA	is inspection	, DIST.	. #3	Date <u>Ju</u>	ine 4	4, 1987	

### NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3 The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven dars.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6 Flow Text No. 2 shall be conducted even though no leak yas indicated during Flow Text No. 1 PHEFOUR FOR TEXT No. 2 is to be the state at the Flow Text No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first how thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Axter District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil 200cs only).