SKELLY OIL COMPANY

Box 426, Farmington, New Mexico May 21, 1956

ante letter

File: Jicarilla "C" Well No. 2



Oil Conservation Commission Attn: Mr. Emery Arnold P. 0. Box 697 Aztec, New Mexico

Dear Sir:

By this letter we are requesting permission to dualcomplete the above captioned well in Section 28-25N-5W, Rio Arriba County. This well was drilled to a total depth of 7220' where the Dakota formation tested dry. We plugged back to 4900" where 5-1/2" casing was run with 2-stage tool was set at 2888'. The Mesa Verde section was cemented with 200 sacks regular cement. Set 7 hrs., ran temperature survey and found top of cement at 4340'. Opened 2-stage tool and cemented Pictured Cliffs formation with 200 sacks cement.

We wish to dual complete this well and plan to perforate the M.V. section from 4642'-4767' where we encountered a good gas show on a drill stem test while drilling the well. We will set a packer, Baker Model D-Production, Product #415-D; 5' production tube with perforations, Type F; Locater tubing seal assembly Model E with 2 seal units, Product #442-E2. We plan to produce the MV section through 2" tubing and will perforate the P.C. section from 2630'-2667' and produce this pay through the annulus. Due to the fact that we have 5-1/2" casing in the hole, it will be impossible to run l" tubingfor siphon string. Our plans are to run Otis side door removable choke in case annulus fills up with fluid we can remove this choke and blow fluid from the hole.

Enclosed are copies of the Schlumberger logs requested by you in our telephone conversation.

Very truly yours,

P. E. Cosper

PEC/st

District Foreman