Form 9-331 b (April 1952)					
	Mrig	15			
		4			
1					

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Indian Ag	ency		
35.gr	ملائه	Tri	bal
	Apart		
	Contin		

	GEOLOGICAL SORVET	Shound Alle
SUNDRY I	NOTICES AND REPORT	rs on wells
NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT SHUT-OFF SUBSEQUENT REPORT REPAIR WELL SUBSEQUENT REPORT CIDIZE SUBSEQUENT REPORT	
(indicate	ABOVE BY CHECK MARK NATURE OF REPORT, NOTIC	Hay 28, , 19 5
/ell No is loca	ted $\frac{129}{129}$ ft. from $\frac{ N }{ N }$ line and $\frac{12}{129}$	ft. from W line of sec.
NK/4 Section 26		M. P. M.
(14 Sec. and Sec. No.)	(Twp.) (Range)	(Meridian)
(Field)	(County or Subdivision)	(State or Territory)
To alamaian af tha danniale	floor above sea level is	
ne elevation of the derrick		
ne elevation of the derrick	DETAILS OF WORK	
	DETAILS OF WORK objective sands; show sizes, weights, and lengths of ing points, and all other important proposed	proposed casings; indicate mudding jobs, cement

Set packer at 4577' - pumped 100 ske. 50% posmin, failed to squeeze. Man, press, 2600f, min, 900f.
Pumped 100 ske. 50% posmin, also failed to squeeze. Man, press, 3500f, min, 1600f. Pumped 75 ske. 50% posmin w/cf filecal per sack. Man, 3500f, min, 1600f. Squeeze successful.

Perforated 5-1/2" ong. at Sallowing intervals: 4690"-4696": 4699"-4733": 4719"-4725": 4729"-4732": 4739"-4741":4744"-4752": 4755"-4767", w/4 bullets per fest for a total of 235 shote. Treated w/May0000 sand, 50,000 sale vator. Used 254 bble to fingh. Breakdown 28000-treating press, 28000-80000, Inj. rate, 46,6 bble/min. Time of treatment, 33 minutes. P.B.T.D. 4830".

I understand that this plan of work must receive approval in writing by the	Geological Survey before operations may be commenced.		
Company SERLIN OIL COMPANY	050		
Address 26,	Sun Call		
Parmington, Now Hard to	By 350		
	Title District errori Co.		
U. S. GOVERNMENT PRINTING OFFICE	1 6 —8437b-8		