

(Orig. Sgd.)	W. LONG
ACTING DISTRICT	ENGINEER

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Indian Agency _____
Alamogordo Indian
Allottee **Alamogordo #0**
Lease No. **Contract #14**
Tract #79

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Alamogordo #0 **June 13,** 19 **56**
Well No. **2** is located **1295** ft. from **N** line and **1295** ft. from **E** line of sec. **20**
N 1/4 Section 20 **25N** **25** **N. M. P. M.**
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Undesignated **El Alamo** **New Mexico**
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is **6977** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

This well was intended to be a dual completion of the Mesa Verde and Pictured Cliffs formations, but due to parting of the 2-1/2" casing at 2140', it was necessary to plug back the Mesa Verde.

This plug was set from 4335' to 4510' with 25 sacks regular cement. Plug back total depth - 4335'.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be started.

Company **SKELLY OIL COMPANY**
Address **P. O. Box 426,**
Farmington, New Mexico

By **J. E.**
Title **District Engineer**

