

Jicarilla 30-2

C-29-25N-4W

Rio Arriba County

* all depths measured from K.B.
(11' above ground level)

Surface Plug: 360' - surface
(120 sx Class B w/2% CaCl_2)

Perts @ 360' to circulate
surface plug

Ojo Alamo Plug: 2540' - 2940'
(45 sx Class B w/2% CaCl_2)

Ojo Alamo 2590'

Calc. Cement Top @ 2750'

Pictured Cliffs Plug: 3190' - 3330'
(16 sx Class B w/2% CaCl_2)

Pictured Cliffs 3242'

6 sx Class B w/2% CaCl_2
on top of retainer (50')

Cement Retainer @ 4900'

Mesa Verde 4913'

Mesa Verde Plug: 4900' - 5560'
(125 sx Class B w/2% CaCl_2 -
50 sx included for perts)

5444' - 76'

5522' - 28'

5540' - 60'

Mesa Verde perts

Cement Top @ 5950'

5 1/2", 15.5#, J-55 Casing

Note: Bottom portion of well was abandoned in 1981 and is not
shown here (original TD - 6946')

Made By

Greg Ashdown

Conoco Inc.

Calculation Sheet

000000

Checked By

Date May 18, 1987

Page

Jicarilla 30-2
P&A Sketch

W. Lindrith
State New Mexico