



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. SP 479601
Unit Lynia Kentz

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	Report of 2nd Perforations	X
	Report of 2nd Squeeze Job	X

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Lynia Kentz December 16, 1957
Well No. 2 is located 1650 ft. from N line and 990 ft. from W line of sec. 19
1/4 Section 19 25N 3W N.M.P.M.
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Blanco - I.C. (Ext.) Rio Arriba New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is _____ ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)
Perforated 7" casing 3659-67' w/4 velox jet shots per ft. Total of 8', 32 holes.
Holes filled approximately 1000' w/sand immediately after perforating.

Run 2" tubing w/Halliburton HNC packer set at 3620'. Squeezed 7" perforations
3659-67' w/100 lbs. reg. cement, 28 lbs. in formation, 14 ft 7 lbs. in 7" casing,
reversed out 15 lbs. BPF 1000#, Max. Squeeze Pressure 4500#, Min. Squeeze
Pressure 1000#.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company _____
Address _____

By _____
Title District Superintendent