

Form 9-881b
(April 1952)

(SUBMIT IN TRIPLICATE)

Indian Agency Mescalito Tribal

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Allottee _____

Lease No. Com. #64, Tract #121

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	<u>Water Fracture</u>	<u>X</u>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

May 7, 19 56

Mescalito
Well No. 1-E is located 1580 ft. from [N] line and 1040 ft. from [E] line of sec. 19
NE Section 19 25N 4E 18W
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Wildcat Rio Arriba New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 7369 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

On 5-3-56 T.D. 3715'. C.O.T.D. 3698'.
Perforated intervals 3646-3660, 3667-3688 with 4 holes jet shots/ft.
Water fractured with 42,500 gallons water, 60,000 gal sand. Flushed with
3700 gallons water. Maximum pressure 2550 psi, Breakdown pressure 2550 psi,
Average treating pressure 2250 psi. Injection rate 44.8 bbls./min.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations are commenced.

Company El Paso Natural Gas Company

Address Box 997
Farmington, New Mexico

By D. C. Johnston
Title Petroleum Engineer