


(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office **Santa Fe**
Lease No. **NM 01476**
Unit **Mexico-Ped "B"**



SUNDRY NOTICES AND REPORTS ON WELLS

| | | |
|--|--|---------------------|
| NOTICE OF INTENTION TO DRILL | SUBSEQUENT REPORT OF WATER SHUT-OFF | Production 1 |
| NOTICE OF INTENTION TO CHANGE PLANS | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING | |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF | SUBSEQUENT REPORT OF ALTERING CASING | |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL | SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR | |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE | SUBSEQUENT REPORT OF ABANDONMENT | |
| NOTICE OF INTENTION TO PULL OR ALTER CASING | SUPPLEMENTARY WELL HISTORY | |
| NOTICE OF INTENTION TO ABANDON WELL | Report of perforations | X |
| | Report of sand-free | X |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

December 7, 1959, 19__

Mexico-Ped "B"
Well No. **1** is located **790** ft. from **S** line and **1450** ft. from **W** line of sec. **18**
Su/A - Section 18 **23N** **2W** **NMZN**
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Ballard - Pictured Cliffs **Mio Arriba County** **New Mexico** **DEC 9 1959**
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is **7676** ft.

U. S. GEOLOGICAL SURVEY
FARMINGTON, NEW MEXICO

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging jobs, cementing points, and all other important proposed work)

Run and set 5-1/2" OD casing at 3890' and cemented with 75 sacks of regular cement 45 gal and 62 sacks (75 cu. ft.) of stratacrete.

Perforated 5-1/2" OD casing with 4 lane Wells jet shots per foot as follows:
3800' - 3850' (50') 200 holes

Frased Pictured Cliffs formation, down 5-1/2" OD casing perforations 3800-3850' with 60,000 gal of 20/40 sand and 45,000 gallons of water. Flushed with 5922 gallons of water. BHP 3350#, maximum treating pressure 1800#, minimum treating pressure 1200#. Injection rate 61.7 BPH.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **SEELY OIL COMPANY**

Address **Box 426**

Farmington, New Mexico

By **(Signed) P. E. Cooper**

Title **District Superintendent**

