

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator
MERIDIAN OIL

3. Address & Phone No. of Operator
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M
1850' FSL, 1850' FWL, Sec.15, T-25-N, R-3-W, NMPM

5. Lease Number
SF-080536
6. If Indian, All. or
Tribe Name
7. Unit Agreement Name
8. Well Name & Number
Hall #6
9. API Well No.
30-039-06010
10. Field and Pool
Basin Fruitland Coal
11. County and State
Rio Arriba Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

<input checked="" type="checkbox"/> Notice of Intent	<input checked="" type="checkbox"/> Abandonment	<input type="checkbox"/> Change of Plans
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion	<input type="checkbox"/> New Construction
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging Back	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Altering Casing	<input type="checkbox"/> Conversion to Injection
	<input type="checkbox"/> Other -	

13. Describe Proposed or Completed Operations

It is intended to plug and abandon the subject well according to the attached procedure and wellbore diagram.

RECEIVED
JUN - 2 1995
OIL CON. DIV.
DIST. 3

14. I hereby certify that the foregoing is true and correct.

Signed [Signature] (ROS9) Title Regulatory Affairs Date 5/11/95

(This space for Federal or State Office use)

APPROVED BY [Signature] Title Chief, Lands and Mineral Resources Date JUN 2 1995

CONDITION OF APPROVAL, if any:

Attached

PLUG & ABANDONMENT PROCEDURE

5-8-95

Hall #6
Basin Fruitland Coal
SW Section 15, T-25-N, R-3-W
Rio Arriba Co., New Mexico

Note: All cement volumes use 100% excess outside pipe and 50' excess inside pipe. The stabilizing wellbore fluid will be 8.3 ppg, sufficient to balance all exposed formation pressures.

1. Install and test location rig anchors. Prepare blow pit. Comply to all NMOCD, BLM, and MOI safety regulations.
2. MOL and RU daylight pulling unit. Conduct safety meeting for all personnel on location. NU relief line. Blow down well and kill with water as necessary. ND wellhead and NU BOP. Test BOP.
3. POH and tally 1-1/4" 2.4# EUE tubing (125 joints w/pinned collar on bottom 3744'); visually inspect the tubing. If necessary, PU 2-3/8" workstring.
4. **Plug #1 (Pictured Cliffs, Fruitland Coal perforations, Kirtland and Ojo Alamo tops, 3752' - 3402')** RIH with open ended tubing and tag CIBP at 3752', or as deep as possible. Pump 15 bbls water. Mix 79 sx Class B cement and spot a balanced plug from 3752' to 3402'. Pull out of hole and WOC. While WOC, PU 5-1/2" casing scraper or wireline gauge ring and round-trip to 2450'. RIH and tag cement. Load well with water and circulate clean. Pressure test casing to 500#. POH with tubing.
5. **Plug #2 (Nacimiento top, 2500' - 2400')**: Perforate 3 or 4 squeeze holes at 2500'. If casing pressure tested, establish rate into squeeze holes. PU 5-1/2" cement retainer and RIH; set at 2450'. Pressure test tubing to 1000#. Establish rate into squeeze holes. Mix and pump 47 sx Class B cement, squeeze 30 sx cement outside casing from 2500' to 2400' and leave 17 sx inside casing to cover Nacimiento top. POH and LD tubing.
6. **Plug #3 (Surface)**: Perforate 2 or 3 squeeze holes at 138'. Establish circulation out bradenhead valve. Mix approximately 38 sx Class B cement and pump down 5-1/2" casing, circulate good cement out bradenhead valve. Shut in well and WOC.
7. ND BOP and cut off wellhead below surface casing flange. Install P&A marker to comply with regulations. RD, MOL, cut off anchors, and restore location.

Recommended: _____
Operations Engineer

Approval: _____
Production Superintendent

Hall #6

CURRENT

Basin Fruitland Coal

SW Section 15, T-25-N, R-3-W, Rio Arriba County, NM

Today's Date: 5/3/95

Spuc: 3/17/59

Completed: 12/29/89

Nacimiento @ 2450'

Ojo Alamo @ 3452'

Kirtland @ 3492'

Fruitland @ 3620'

Pictured Cliffs @ 3738'

12-1/4" hole

8-5/8", 24.0#, J-55, Csg set @ 88',
Cmt w/70 sx (Circulated to Surface)

Top of Cmt @ 3090' (CBL)

125 jts 1-1/4", 2.4#, j-55, EUE, 10rd, tbg set @ 3744',
(w/pinned collar on bottom)

Fruitland Coal Perforations:
3641' - 3738', Total 66 holes

CIBP @ 3752'

Pictured Cliffs Perforations:
3806' - 12', Total 24 holes

5-1/2", 15.5#, J-55, Csg set @ 3896',
Cmt w/100 sx

7-7/8" hole

PBTD 3752'

TD 3904'

Hall #6

Proposed P & A
Basin Fruitland Coal

SW Section 15, T-25-N, R-3-W, Rio Arriba County, NM

Today's Date: 5/8/95

Spud: 3/17/59

Completed: 12/29/89

