

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Budget Bureau No. 42-R358.4.
Approval expires 12-31-60.

Land Office Santa Fe
Lease No. 88-08539
Unit N. P. Hart

SUNDRY NOTICES AND REPORTS ON WELLS

| | |
|--|--|
| NOTICE OF INTENTION TO DRILL | SUBSEQUENT REPORT OF WATER SHUT-OFF |
| NOTICE OF INTENTION TO CHANGE PLANS | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF | SUBSEQUENT REPORT OF ALTERING CASING |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL | SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE | SUBSEQUENT REPORT OF ABANDONMENT |
| NOTICE OF INTENTION TO PULL OR ALTER CASING | SUPPLEMENTARY WELL HISTORY |
| NOTICE OF INTENTION TO ABANDON WELL | <u>Report of Squeeze Job</u> |


(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

N. P. Hart
Well No. 1 is located 795 ft. from N line and 1650 ft. from W line of sec. 13
1/4 Section 13 (1/4 Sec. and 1/4 Sec. No.) 25N 3E N.M.P.M.
(Twp.) (Range) (Meridian)
Undesignated (Kam Verde) Ala. Arriba New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 7324 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging jobs, cementing points, and all other important proposed work)
Run 2" OAB tubing with Halliburton DC cement retainer set at 5396'. Squeezed 5" casing perforations 5462-5524', 5534-40', 5592-5604' & 5660-90' with 200 shocks cement. BOP 5000, maximum & squeeze pressure 12000.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company _____
Address _____

By _____
Title District Superintendent