Form 9-330
(Rev. 5-63)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN DUPLICATE* (See other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R355.5.

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

1a. TYPE OF WELL: OIL WELL [X] GAS WELL [ ] DRY [ ] Other

b. TYPE OF COMPLETION: NEW WELL [ ] WORK OVER [X] DEEP-EN [ ] PLUG BACK [X] DIFF. RESVR. [X] Other

2. NAME OF OPERATOR
Amoco Production Company

3. ADDRESS OF OPERATOR
501 Airport Drive Farmington, NM 87401

4. LOCATION OF WELL (*Report location clearly and in accordance with any State requirements*)*
At surface 1005 FNL x 1750 FWL Sec 15, T25N, R5W
At top prod. interval reported below Same
At total depth Same

5. LEASE DESIGNATION AND SERIAL NO.
Jicarilla Contract 148

6. IF INDIAN, ALLOTTEE OR TRIBE NAME
Jicarilla Tribal

7. UNIT AGREEMENT NAME
Jicarilla Contract 148

8. FARM OR LEASE NAME
30-039-06662

9. WELL NO.
#13

10. FIELD AND POOL, OR WILDCAT
Otero Gallup

11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA
NE/4 NW/4 Section 15
T25N, R5W

14. PERMIT NO. | DATE ISSUED

12. COUNTY OR PARISH: Rio Arriba | 13. STATE: NM

15. DATE SPUDDED	16. DATE T.D. REACHED	17. DATE COMPL. (*Ready to prod.*)	18. ELEVATIONS (DF, RKB, RT, GR, ETC.)*	19. ELEV. CASINGHEAD
6-19-61	7-10-1961	5-29-80	7020 KB	

20. TOTAL DEPTH, MD & TVD	21. PLUG, BACK T.D., MD & TVD	22. IF MULTIPLE COMPL., HOW MANY*	23. INTERVALS DRILLED BY	ROTARY TOOLS	CABLE TOOLS
7537	7331		→	0 TD	

24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)* 6726-6734, 6743-6748, 6760-6769, 6774-6786, 6820-6842, 6854-6860, 6865-6868, 6876-6890, 6902-6910, 6919-6926, 6566-6588, 6604-6626, 6642-6658, 6672-6678, Otero Gallup

25. WAS DIRECTIONAL SURVEY MADE: No

26. TYPE ELECTRIC AND OTHER LOGS RUN
Electrical Survey

27. WAS WELL CORED: No

28. CASING RECORD (*Report all strings set in well*)

CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8-5/8"	24#	506'	12-1/4"	375 sx	--
4-1/2"	9.5#	7537'	7-7/8"	700 sx	--

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)

30. TUBING RECORD

SIZE	DEPTH SET (MD)	PACKER SET (MD)
2-3/8"	6996'	

31. PERFORATION RECORD (*Interval, size and number*)
6726-6926, with 2 spf, a total of 174, .38" holes.
6566-6678 with 2 spf, a total of 88, .38" holes.

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
6726-6926	117,501 gal of frac fluid x
	294,340# of 20-40 sand
6566-6678	72,499 gal of frac fluid x
	206,660# of 20-40 sand

33.* PRODUCTION

DATE FIRST PRODUCTION	PRODUCTION METHOD (*Flowing, gas lift, pumping—size and type of pump*)	WELL STATUS (*Producing or shut-in*)
7-13-80	Pumping	Producing

DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N. FOR TEST PERIOD →	OIL—BBL.	GAS—MCF.	WATER—BBL.	GAS-OIL RATIO
7-1-80	24	Open		6	74	14	12,300

FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE →	OIL—BBL.	GAS—MCF.	WATER—BBL.	OIL GRAVITY-API (CORR.)
50 psig	--		6	74	14	.71

34. DISPOSITION OF GAS (*Sold, used for fuel, vented, etc.*)
To be sold

TEST WITNESSED BY

35. LIST OF ATTACHMENTS

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED (Original Signed By) E. S. OBODA TITLE District Administrative Supervisor DATE August 1 1980

*(See Instructions and Spaces for Additional Data on Reverse Side)

INSTRUCTIONS

General: This form is designed for submitting a complete and correct well completion report and log on all types of lands and leases to either a Federal agency or a State agency, or both, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office. See instructions on items 22 and 24, and 33, below regarding separate reports for separate completions.

If not filed prior to the time this summary record is submitted, copies of all currently available logs (drillers, geologists, sample and core analysis, all types electric, etc.), formation and pressure tests, and directional surveys, should be attached hereto, to the extent required by applicable Federal and/or State laws and regulations. All attachments should be listed on this form, see item 35.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 18: Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments.

Items 22 and 24: If this well is completed for separate production from more than one interval zone (multiple completion), so state in item 22, and in item 24 show the producing interval, or intervals, top(s), bottom(s) and name(s) (if any) for only the interval reported in item 33. Submit a separate report (page) on this form, adequately identified, for each additional interval to be separately produced, showing the additional data pertinent to such interval.

Item 29: *"Sacks Cement":* Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool.

Item 33: Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 24 above.)

37. SUMMARY OF POROUS ZONES: SHOW ALL IMPORTANT ZONES OF POROSITY AND CONTENTS THEREOF; CORED INTERVALS; AND ALL DRILL-STEM TESTS, INCLUDING DEPTH INTERVAL TESTED, CUSHION USED, TIME TOOL OPEN, FLOWING AND SHUT-IN PRESSURES, AND RECOVERIES				38. GEOLOGIC MARKERS		
FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	TOP	
					MEAS. DEPTH	TRUE VERT. DEPTH
	2645'	2845'	fairly clean sandstone			
Kirtland	2845'	3040'	shale with thin sandstone streak			
Fruitland	3040'	3200'	coal, shale and sand			
Pictured Cliffs	3200'	3280'	shaly sandstone			
Chacra	4090'	4130'	shaly sandstone			
Mesaverde	4875'	5598'	shale and shaly sandstone			
Mancos	5598'	7400'	shale			
Gallup	6450'	7130'	laminated sandstone and shale			
Greenhorn	7345'	7400'	limestone			
Graneros	7422'	7475'	shaly sandstone			

U.S. GOVERNMENT PRINTING OFFICE: 1963—O-683036

GPO 680-147