(May 196.)	DEPARTM	UNITED STATES LENT OF THE INTER	SUBMIT IN TRIPLICAT HOR (Other instructions on verse side)	re- 5. DEASE DESIGNATION AND SERVE NO.
GEOLOGICAL SURVEY SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)				6. IF INDIAN, ALLOYTEE OR TRIBE NAME.
1. OIL S GAS OTHER				Jicarilla Apache 7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR Continental Oil Company 3. ADDRESS OF OPERATOR				S. FARM OR LEASH NAME Jicarilla 28 9. WELL NO.
200 North Wolcott, Casper, Wyoming 82601 4. Location of Well (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 710' FNL, 660' FWL				10. FIELD AND POOL, OR WHITE AT Undesignated Gallup Undesignated Dakon: 11. SEC., T., E., M., OR BLE, AND SURVEY OR AREA
14. PERMIT NO.		15. ELEVATIONS (Show whether D	F, RT, GR, etc.)	Section 33, T25N, R49
		6835' Gr., 6848' RB		Rio Arriba New Mexico
16.	Check Ap	propriate Box To Indicate 1	Nature of Notice, Report, or	
	NOTICE OF INTENT		t.	EQUENT REPORT OF:
FRACTURE TREASHOOT OR ACIDE REPAIR WELL (Other) 17. DESCRIBE PROPERS proposed worl nent to this we	T M M TE AI CH SEP OR COMPLETED OPER k. If well is direction	CLL OR ALTER CASING ULTIPLE COMPLETE BANDON* HANGE PLANS ATIONS (Clearly state all pertiner ally drilled, give subsurface loce	water shut-off fracture treatment shooting or acidizing (Other) Casir (Note: Report resu Completion or Recor	BEPAIRING WELL ALTERING CASING ABANDONMENT* Its of multiple completion on Well mpletion Report and Log form.) es, including estimated date of starting any tical depths for all markers and zones perti-
7606'. 5 with 350 sa Opened stay 120 sacks 6 1/4# of 0	1/2" OD, 14#, acks of 1-1 Pege collar at laight weight of Gilsonite per	15.5#, and 17# cas ozmix with 2% gel, 5445'. Circulated cement followed by sack. Plug down 6	12:15 A.M., 11-24-6 ing set at 7606' and .5 of 1% D65 and 6 1 3 1/2 hours. Cement 300 sacks 1-1 Pozmix	I and cemented with 165 8. Drilled to total depth cemented through shoo ./4% of Gilsonite per sack. ded through stage coller with 1, 2% gel, .5 of 1% D65 and Each cement job preceded
÷			RECEIVED	D \(\begin{array}{c} \begin{array}{c} \b
			*	VEY VERSE SEE SEE
			U. S. GEOLOGICAL SUR FARMINGTON, N. M.	- (B) (1980)
USGS-Farmington(3) NMOCC(2) File				DIST COM
18. I hereby certify	that the foregoing is	true and correct		3 3 3
SIGNED	And the second second	TITLE Adn	ninistrative Sec. Ch	ief DATE 12-24-58
(This space for	Federal or State office	use)		
APPROVED BY CONDITIONS OF	F APPROVAL, IF AN	Y:		DATE CONTROL OF THE C