

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐  
2. NAME OF OPERATOR  
CONOCO INC.  
3. ADDRESS OF OPERATOR  
P. O. Box 460, Hobbs, N.M. 88240  
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1980' FL, 1980' FEL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:  
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:  
TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) \_\_\_\_\_

SUBSEQUENT REPORT OF:

☐  
☐  
☒  
☐  
☐  
☐  
☐  
☐  
☐

5. LEASE  
Contract 66  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
Ticarilla Apache  
7. UNIT AGREEMENT NAME  
8. FARM OR LEASE NAME  
Ticarilla 28  
9. WELL NO.  
7  
10. FIELD OR WILDCAT NAME  
W. Lindrith Gallup Dakota  
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 27, T-25N, R-4W  
12. COUNTY OR PARISH  
Rio Arriba  
13. STATE  
NM  
14. API NO.  
15. ELEVATIONS (SHOW DF, KDB, AND WD)

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

10/14/80 - MIRE. Kill well. With w/ tbg, tagged bottom at 7734'. POOH. Spd 2000 gals  
15% HCl-NE-FE. Perf 6629', 30', 31', 32', 33', 34', 90', 6786', 87, 88', 6804', 24', 77', 78', 7445', 46',  
53', 57', 62', 63', 72', 75', 77', 7516', 45', 7628', 29', 30', 31', 32', 42', 43', 44', 49', 52', 7702', 04', 07',  
7710'. total 39 holes with w/ tbg, swbd well. Pmpd 2000 gals HCl, Flushed w/ 31 bbl  
produced wtr. swabbed load. Placed well on test.  
Well tested 280, 1/2 BW, 62 MCF on 11/14/80.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_

Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED D. E. Bingham TITLE Senior Analyst DATE Nov. 18, 1980

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

TITLE \_\_\_\_\_ DATE \_\_\_\_\_

USGS 5  
BEA 1  
MIL 1  
FILE 1