

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1 ✓
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name <b>Canyon Largo Unit</b>
2. Name of Operator <b>El Paso Natural Gas Company</b>	8. Farm or Lease Name <b>Canyon Largo Unit</b>
3. Address of Operator <b>Box 990, Farmington, New Mexico - 87401</b>	9. Well No. <b>145</b>
4. Location of Well UNIT LETTER <b>M</b> <b>1050</b> FEET FROM THE <b>South</b> LINE AND <b>990</b> FEET FROM THE <b>West</b> LINE, SECTION <b>2</b> TOWNSHIP <b>24N</b> RANGE <b>7W</b> NMPM.	10. Field and Pool, or Wildcat <b>Ballard P. C.</b>
15. Elevation (Show whether DF, RT, GR, etc.) <b>6952' GL</b>	12. County <b>Rio Arriba</b>

### Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

#### NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

#### SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <b>Perf &amp; S/W Frac</b> <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

On 6-24-69 spudded well, drilled surface hole.

On 6-25-69 ran 4 joints 8 5/8", 24#, K-55 casing (127') set at ground level w/85 sacks of cement circulated to surface. W.O.C. 12 hours, held 600#/30 Min.

On 6-30-69 T. D. 2601', ran 88 joints 2 7/8", 6.4#, J-55 casing (2590') set at 2601' w/175 sacks of cement. W.O.C. until completion.

On 7-15-69 P.B.T.D. 2591', perf. 2481-2497' w/2 SPF. Sand water frac w/30,000# 10/20 sand, 27,040 gal. water, flushed w/700 gal. water, no balls dropped.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Original Signed By:

SIGNED L. O. Van Ryan TITLE Oil Petroleum Engineer DATE 7-17-69

APPROVED BY Emory Clavel TITLE SUPERVISOR DIST. #3 DATE JUL 23 1969

CONDITIONS OF APPROVAL, IF ANY: