	1
UNITED STATES (May 1963)  UNITED STATES (Other instructions on report of the instructions of the instruction of t	Form approved. Budget Bureau No. 42-R1424 5. LEASE DESIGNATION AND SERIAL NO.
GEOLOGICAL SURVEY	Contract 147
SUNDRY NOTICES AND REPORTS ON WELLS  (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  Use "APPLICATION FOR PERMIT—" for such proposals.)	6. IF INDIAN, ALLOTTEE OR TRIBE NAME  Jicarilla Apache
1. OIL GAS X OTHER	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR	8. FABM OR LEASE NAME
Continental Oil Company	AXI Apache "J"
	9. WELL NO.
152 North Durbin, Casper, Wyoming 82601	19
	10. FIELD AND POOL, OR WILDCAT Undesignated Mesaverd
NW NW 990' FNL, 990' FWL	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

VILDCAT Mesaverde AND (Unit Letter "D") Sec. 6, T25N, R5W 12. COUNTY OR PARISH 13. STATE 15. ELEVATIONS (Show whether DF, RT, GR, etc.) 14. PERMIT NO. 6584 Grd., 6596 KB-Measuring Point Rio Arriba New Mexico Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data 16. SUBSEQUENT REPORT OF: NOTICE OF INTENTION TO: TEST WATER SHUT-OFF PULL OR ALTER CASING WATER SHUT-OFF REPAIRING WELL FRACTURE TREATMENT ALTERING CASING MULTIPLE COMPLETE FRACTURE TREAT ARANDON MENT SHOOTING OR ACIDIZING ABANDON\* SHOOT OR ACIDIZE Casing Run CHANGE PLANS (Other) -REPAIR WELL (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) (Other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\* Spudded 11-8-71. 8 5/8", 24# casing set at 239' and cemented with 150 sacks Class "A" with 2% CaCl2. Drilled to TD 5268' and ran IES, GR-FDC logs. Set 5 1/2", 14# casing at 5267' KB and cemented with 1st stage 235 sacks 50-50 Pozmix with 2% gel, 6 1/4"/sack Gilsonite and 1/2% D-31 followed by 275 sacks of the same cement for the second stage. Plug down at 6:45 AM, 11-18-71. WOC. Drilled out stage collar at 3775' and ran tubing. Released rig 11-19-71. Waiting on completion rig to complete the well.

File(2) Humble Oil Co. USGS(6) 18. I hereby certify that the foregoing is true and correct TITLE Administrative Supervisor DATE \_ 11-23-71 (This space for Federal or State office use) APPROVED BY DATE . CONDITIONS OF APPROVAL, IF ANY:

U.S.