Form	9-331
(May	1963)

## UNITED STATES SUBMIT IN TRIPLICATE\* DEPARTMENT OF THE INTERIOR (Other instructions on reverse side)

Form approved. Budget Bureau No. 42-R1424. 5. LEASE DESIGNATION AND SERIAL NO.

<b></b>	GEOLOGICAL SURVEY	Contract No. 147
(Do not use this form for	NOTICES AND REPORTS ON WELLS  proposals to drill or to deepen or plug back to a different reservoir.  PPLICATION FOR PERMIT—" for such proposals.)	6. IF INDIAN, ALLOTTEE OR TRIBE NAME  Jicarilla Apache
OIL GAS WELL OT	HER	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR		8. FARM OR LEASE NAME
Co	ontinental Oil Company	AXI Apache "J"
3. ADDRESS OF OPERATOR		9. WELL NO.
1	52 North Durbin, Casper, Wyo. 82601	25
4. LOCATION OF WELL (Report loc See also space 17 below.) At surface	ation clearly and in accordance with any State requirements.*	10. FIELD AND POOL, OR WILDCAT AXI Apache - Otero Chacr Undesignated Mesaverde
6	60' FNL, 660' FEL ("A")	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
		Sec. 7, T25N, R5W
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.)	12. COUNTY OR PARISH 13. STATE
	6704 GR, 6716 KB	Rio Arriba New Mexico
18. Che	ck Appropriate Box To Indicate Nature of Notice, Report, o	r Other Data

SUBSEQUENT REPORT OF: NOTICE OF INTENTION TO:

		1	1		1
TEST WATER SHCT-OFF	PULL OR ALTER CASING		WATER SHUT-OFF	REPAIRING WELL	<u> </u> —
FRACTURE TREAT	MULTIPLE COMPLETE		PRACTURE TREATMENT	ALTERING CASING	
SHOOT OR ACIDIZE	ABANDON*		SHOOTING OR ACIDIZING	ABANDONMENT*	
REPAIR WELL	CHANGE PLANS		(Other)	Casing Run	X
(Other)			(Note: Report resu Completion or Reco	ilts of multiple completion on Wel mpletion Report and Log form.)	1

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) •

Spudded 1-10-72, drilled to TD 5300\*, PBTD 5246\*. Ran 8 5/8" 24# K-55 casing set at 227' and cemented with 150 sacks Class "A" and 2% CaCl2. Ran 5 1/2" 14# casing landed at 5299' with float collar at 5266' and stage collar at 3920'. Preceded first cement stage with 250 gallon Pre-Flush and cemented with 180 sacks 50-50 Poz "A", 2% gel, 64 / sack Gilsonite and 1/2% D-31. Preceded second stage with 250 gal. Pre-Flush and cemented with 315 sacks as first stage. Plug down 4:15 p.m. 1-19-72. Rig released 1-20-72.



USGS-Durango(6) Humble Oil Fil	le(2)	
18. I hereby certify that the foregoing is true and correct SIGNED —		DATE3-14-72
(This space for Federal or State office use)		
APPROVED BYCONDITIONS OF APPROVAL, IF ANY:	TITLE	DATE