				1
orm 9-331 May 1963)	U	NITED STATES	SUBMIT IN TRIPLICATE* (Other instructions on re-	Form approved. Budget Bureau No. 42-R1424.
May 1303/	DEPARTMENT OF THE INTERIOR (Other Instructions on re-			5. LEASE DESIGNATION AND SERIAL NO.
	G	OLOGICAL SURVEY		Contract No. 41
SUNDRY NOTICES AND REPORTS ON WELLS				6. IF INDIAN, ALLOTTEE OR TRIBE NAME
	SUNDRY NOTIC	e to drill or to deepen or plug b	ack to a different reservoir.	
(Do not us	Use "APPLICAT	s to drill or to deepen or plug b ION FOR PERMIT—" for such pr	oposals.)	Jicarilla Apache
. <u>.                                   </u>				7. UNIT AGREEMENT NAME
	VELL OTHER			
2. NAME OF OPERATOR				8. FARM OR LEASE NAME
Continental Oil Company				Jicarilla 30
3. ADDRESS OF OPERATOR				9. WELL NO.
	152	North Durhin Casp	er. Wvo. 82601	5
152 North Durbin, Casper, Wyo. 82601  4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*				W. Lindrith - Undesignate
See also space 17 below.) At surface				· F
800' FNL, 1850' FEL ("B")				Gallup and Dakota  11. SEC., T., R., M., OR BLK. AND SUBVEY OR AREA
	000	11.2, 2000 0 a.a. ( )	-	
				Sec. 32, T25N, R4W
14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.)				12. COUNTY OR PARISH 13. STATE
6855' GR, 6869' KB			Rio Arriba New Mexico	
16.	Check Ap	propriate Box To Indicate N	lature of Notice, Report, or (	Jiher Data
NOTICE OF INTENTION TO:				UENT REPORT OF:
		CLL OR ALTER CASING	WATER SHUT-OFF	REPAIRING WELL
TEST WATER	-	CLTIPLE COMPLETE	FRACTURE TREATMENT	ALTERING CASING
FRACTURE TRE		BANDON®	SHOOTING OR ACIDIZING	ABANDONMENT*
SHOOT OR ACI		HANGE PLANS	(Other)	Casing Run X
REPAIR WELL			(Norm: Report result:	s of multiple completion on Well pletion Report and Log form.)
(Other)	and the country of th	itions (4'learly state all pertinell	a diameter dutes	including estimated date of starting any
17. DESCRIBE PROP proposed we nent to this	ork. If well is direction	ally drilled, give subsurface loca	tions and measured and true vertice	al depths for all markers and zones perti-
Emirata a d	1-72 drillad	to 170 75251 PR1D 7	498¹ Ran 8 5/8" 24 <i>i</i>	K-55 casing set at 244
spudded 2-	tod vith 150 ca	cke Clase "A" and 2	% CaClo. Ran 4 1/2"	10.5# K-55 casing set
and cement	ed with 130 88	er at 7498° and sta	se collar at 5336'.	Cemented first stage with
425 acales	FO. SO Poz "A!	1 2 7 4 5 4 4 5 4 4 4 5 4 4 4 5 4 5 4 5 4 5	ack Gilsonite and 1/2	2% CFR-2. Cemented second
433 Sacks	- 200 aceks HT 4	+0-W+ " w/1/29 CFR-	2 and 565 sacks as i	n first stage. Both stages
stage with	1 ZUU SACKS LI	I Mad Fluch ! Pluc	down 5:45 n.m. 2-13:	-72. Rig released 2-13-72.
preceded v	With 500 gailor	mud ridshi. Ilag	down 5.45 p.m. = 20	
				1 120
				COTTO TO
				VIII I I I I I I I I I I I I I I I I I
			ì	RELIE 1917
				201911
				8 900