

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

SF 078922

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Canyon Largo Unit

8. FARM OR LEASE NAME

Canyon Largo Unit

9. WELL NO.

221

10. FIELD AND POOL, OR WILDCAT

Ballard Pictured Cliffs

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREASec. 3, T-24-N, R-7-W
NMPM

12. COUNTY OR PARISH

Rio Arriba

13. STATE

NM

1.

OIL ☐ GAS ☒
WELL WELL OTHER

2. NAME OF OPERATOR

El Paso Natural Gas Company

3. ADDRESS OF OPERATOR

PO Box 990, Farmington, NM 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

1800'N, 810'W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

7050'GL

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐

PULL OR ALTER CASING

☐
☐
☐
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☒
☒
☐

REPAIRING WELL

☐
☐
☐
☐

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

8-23-73 Tested surface casing, held 600#/30 minutes.

8-25-73 TD 2720'. Ran 88 joints 2 7/8", 6.4#, J-55 production casing, 2710' set at 2720'. Baffle set at 2709'. Cemented with 242 cu. ft. cement. WOC 18 hours
Top of cement at 1650'.

9-28-73 Tested casing, held 4000#. PBTD 2709'. Perf'd 2576-2600' and 2610-20' with 26 shots per zone. Frac'd with 40,000# 10/20 sand and 40,210 gallons treated water. Dropped one set of 26 balls. Flushed with 700 gallons water.



18. I hereby certify that the foregoing is true and correct

SIGNED

A. J. Dwyer

TITLE

Drilling Clerk

DATE

October 2, 1973

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

St
*See Instructions on Reverse Side