ADDRESS OF OPERATOR

UNITED STATES DEPARTMENT OF THE INTERIOR (Other Instructions on reverse side)

SUBMIT IN TRIPLICATES

Form approved, Budget Bureau No. 42-R1/24. 5. LEASE DESIGNATION AND SERIAL

SF078885 6. IF INDIAN, ALLOTTEE OR TRIBE NAME

GEOLOGICAL	SURVEY
------------	--------

	SUN	IDRY	NOTICES	AND	REPORTS	ON	WELLS	
(Do not	use this	form form form	or proposals to APPLICATION	drill or to FOR PERI	deepen or plug MIT" for ruch	back to proposal:	a different s.)	reservoir.

7. UNIT AGREEMENT NAME

WELL NO.

278

WELL GAS A OTHER	Canyon Largo Unit
NAME OF OPERATOR	8. FARM OR LEAST NAME
El Paso Natural Gas Company	Canyon Largo Unit

P. O. Box 990, Farmington, New Mexico 87401

LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) 10. FIELD AND POOL, OR WILDCAT Basin Dakota At surface

1960'S, 1820'W

CONDITIONS OF APPROVAL, IF ANY:

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 11, T-25-N, R-6-W N.M.P.M.

14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6678' GL

12. COUNTY OR PARISH 13. STATE lRio Arriba New Mexico

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:			SUBSEQUENT REPORT OF:					
TEST WATER SHUT-OFF		PULL OR ALTER CASING			WATER SHUT-OFF	X	REPAIRING WELL	_
FRACTURE TREAT	_	MULTIPLE COMPLETE			FRACTURE TREATMENT	<u>X</u>	ALTERING CASING	
SHOOT OR ACIDIZE		ABANDON*			SHOOTING OR ACIDIZING		ABANDONMENT*	_
REPAIR WELL	L	CHANGE PLANS			(Other)			
(Other)			<u> </u>		(NOTE: Report res Completion or Reco	uits of ompleth	multiple completion on Well on Report and Log form.)	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

06-26-74 T.D. 7283'. Ran 236 joints 4 1/2" 10.5 and 11.6#, KS production casing; 7270' set at 7283'. Float collar set at 7268'. Stage tool set at 5252'. Cemented first stage with 357 cu. ft. cement; second stage with 1433 cu. ft. cement. WOC 18 hours. Top of cement at 1620'.

09 - 03 - 74Tested casing to 4000#--OK. Perf'd 7018', 7100', 7111', PBTD 7267'. 7125', 7140' and 7175' with 1 shot per zone. Frac'd with 65,000# 40/60 sand and 64,100 gallons treated water. Dropped no balls. Flushed with 4830 gallons water.

			100		
18. I hereby certify that the foregoing is true and correct SIGNED	TITLE	Drilling Clerk		DATE	September 4, 197
(This space for Federal or State office use)					
APPROVED BY	TITLE		· ·	DATE _	·