UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

. 1973	Budget Bureau No. 42-R1424		
UNITED STATES	5. LEASE NM-23043		
DEPARTMENT OF THE INTERIOR			
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME		
voir. Use Form 9-331-C for such proposals.)	8. FARM OR LEASE NAME Schalk 43		
well gas XX other	9. WELL NO.		
NAME OF OPERATOR	# 2		
SCHALK DEVELOPMENT COMPANY ADDRESS OF OPERATOR	10. FIELD OR WILDCAT NAME Wildcat		
P.O. BOX 25825 /ALBUQUEROUE, NM 87125	11. SEC., T., R., M., OR BLK. AND SURVEY OR		
LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA		
below.) 790'FNL; 790'FEL, Sec. 34, T25N,	Sec. 34, T25N, R3W		
AT SURFACE: R3W, Rio Arriba, NM	12. COUNTY OR PARISH 13. STATE		
AT TOP PROD. INTERVAL: 'AT TOTAL DEPTH:	Rio Arriba New Mexico		
	14 . API NO.		
CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,			
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)		
UEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	7213 GR		
T WATER SHUT-OFF			
CTURE TREAT			
OOT OR ACIDIZE			
AIR WELL	(NOTE: Report results of multiple completion or zone		
L OK WEIER CASING	change on Form 9-330.)		

R3W, Rio Arriba, NM AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTIC

REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other) Drilling

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Ran 4-1/2" 10.5# casing set @ 6100' KBM. Cemented 1st stage with 235 sxs. Howco Lite Class'B' w/12-1/4# Gilsonite/sx. 11/7/79 and followed with 330 sxs. 50/50 Pos Mix Class 'B' with 2% C.C., 7# Salt; 6-1/4# Gilsonite/sx. Cemented 2nd Stage with 280 sxs. 50/50 Pos mix Class 'B' with 2% c.c., 7# Salt, 6-1/4# Gilsonite/sx.

17 4 9 1070°

		1 TO 1519.			
Subsurface Safety Valve: Manu. ar	nd Type	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Set @ _	<u> </u>	_ Ft.
18 I hereby certify that the thrego		Partne Toate_	11/9/79		
	(This space for Federal or Stat	te office use)			
APPROVED BY	TITLE	DATE			