

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐

2. NAME OF OPERATOR

Amoco Production Company

3. ADDRESS OF OPERATOR

501 Airport Drive, Farmington, NM 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1840' FNL x 1800' FEL

AT TOP PROD. INTERVAL: same

AT TOTAL DEPTH: same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) ☐ Completion ☒

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐
☐
☐

5. LEASE

Jicarilla Contract 125

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Jicarilla Apache

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Jicarilla Apache Tribal 125

9. WELL NO.

8

10. FIELD OR WILDCAT NAME

Lindrith Gallup-Dakota West

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

SW/4, NE/4, Section 26, T25N, R4W

12. COUNTY OR PARISH

Rio Arriba

13. STATE

NM

14. API NO.

30-039-22353


15. ELEVATIONS (SHOW DF, KDB, AND WD)

7041' GL

RECEIVED

SEP 11 1980

(Note: Report results of multiple completion or zone change on Form 9-330)
U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Completion operations commenced on 7-24-80. Total depth of the well is 7966' and plug back depth is 7910'. Perforated interval from 7588-7596', 7600-7616', 7646-7654', 7729-7735', 7762-7788', with 2 SPF, a total of 128, .40" holes. Sand water fraced with 116,000 gal of frac fluid and 392,000# of 20-40 sand. Perforated interval from 6710-6744', 6752-6753', 6981-6994', 7033-7044', 7050-7054, with 2 SPF, a total of 336, .40" holes. Sand water fraced with 186,000 gal of frac fluid and 630,500# of 20-40 sand. Landed 2-7/8" tubing at 7044'. Swabbed the well and released the rig on 8-25-80.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED _____ TITLE Dist. Adm. Supvr. DATE 9-5-80

ACCEPTED FOR RECORD

(This space for Federal or State office use)

APPROVED BY SEP 11 1980
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____ DATE _____

BY BA FARMINGTON DISTRICT

NMOCC