Form 9**-331** (May 1963)

OIL U

NAME OF OPERATOR

ADDRESS OF OPERATOR

GAS WELL

|X|

KENAI OIL AND GAS INC.

UNITED STATES DEPARTMENT OF THE INTERIOR (Other instructions on reverse side) GEOLOGICAL SURVEY

717 17th Street, Suite 2000, Denver, Colorado 80202 LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)

At surface

SUBMIT IN TRIPLICATE.

Budget Bureau No. 42-R1424

NM-23032					SERIA	∥ NO.		
6.	IF	IND	IAN,	ALLOTTE	E OR	TRIBE	NAME	

SUNDRY NOTICES	AND REPORTS	ON WELLS
use this form for proposals to	o drill or to deepen or plug	back to a different reservoir

NONE

7.	UNIT	AGR	EEM	ENT	NAME	
	NO					

NO	١E		
 FARM	OR	LEASE	NAME

FEDERAL 5

9. WELL NO. #43

10. FIELD AND POOL, OR WILDCAT Gavilan Pictured Cliffs

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 2, T24N-R2W

12. COUNTY OR PARISH | 13. STATE

14. PERMIT NO.

(Other)

16.

15. ELEVATIONS (Show whether DF, RT, GR. etc.) 7285' GL

Rio Arriba

SUBSECUENT REPORT OF :

NM

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO: PULL OR ALTER CASING TEST WATER SHUT-OFF MULTIPLE COMPLETE FRACTURE TREAT SHOOT OR ACIDIZE CHANGE PLANS REPAIR WELL

1650' FSL - 790' FEL (NESE)

WATER SHUT-OFF FRACTURE TREATMENT REPAIRING WELL ALTERING CARING

BROOTING OR ACIDIZING LABANDONM
tatus: Drilling or completing

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

MIRU Corrosion Control Rig #1, Drilled 12-1/4" hole to 220' GL, lost circ, 12/26/79: mixed gel & LCM & regained returns.

12/27/79: TD 220' GL. Ran 5 jts., 8-5/8", 23#, J-8RT-STC-R3 new csg. w/guide shoe & insert float collar, total length 212.70'. Landed csg @ 214' GL & cemented by B-J w/250 sxs. Class B cement, plus 2% Calcium Chloride & 1/4# Cello-Flake /sx. Full returns while cementing. PD @ 3:30 a.m., 12/27/79. Circ. cement.

12/28/79: WOC - cement fell back 2' will release rig @ noon today.



18. I hereby certify that the foregoing is true and	correct	
SIGNED THE TOTAL OF	TITLE Manager-Drilling & Production ATE	12/28/79
<u> </u>		
(This space for Federal or State office use)		
APPROVED BY	TITLE DATE	l

*See Instructions on Reverse Side