

6 - USGS 1 - McHugh 1 - Kenai O & G 1 - File

Form 9-331
Dec. 1973

Form Approved.
Budget Bureau No. 42-R1424

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☐ other ☒ Dry Hole

2. NAME OF OPERATOR

Jerome P. McHugh

3. ADDRESS OF OPERATOR

P O Box 208, Farmington, NM 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 790' FNL - 1850' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☒
(other) ☒

SUBSEQUENT REPORT OF:

RECEIVED
JUL 16 1981
U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

(NOTE: Report results of multiple completion zone change on Form 9-330.)



5. LEASE

NM 23033

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal

9. WELL NO.

31

10. FIELD OR WILDCAT NAME

Undesignated

11. Undesignated, OR BLK. AND SURVEY OR AREA

Sec 3 T24N R2W

12. COUNTY OR PARISH

Rio Arriba

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

7235' GL

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS* (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plan to plug and abandon this well as follows:

1. Spot cement plug top of Baker Retainer 3300' to 3000' (50' above top of Ojo Alamo at 3050')
2. Spot cement plug 2896 - 2720'.
3. Spot cement plug 2573 - 2466'.
4. Shoot off 4 1/2" csg. at free point.
5. Spot cement plug 50' in and 50' out of csg. stub.
6. Place 100' cement plug in bottom of surface. *from 262' to 162'*
7. Place 50' plug in top of surface pipe and install dry hole marker.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED _____ Jim L. Jacobs TITLE Agent DATE 7-16-81

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

al

NMOCC

*See Instructions on Reverse Side

