Approved as to plugging of the well bore. Liability under bond is retained until surface restoration is completed.

6 - USGS, Fmn 1 McHugh  Form 9-331 Dec. 1973	Form Approved.  Budget Bureau No. 42-R1424
UNITED STATES	5. LEASE
DEPARTMENT OF THE INTERIOR	NM 23038  6. IF INDIAN, ALLOTTEE OR TRIBE NAME
GEOLOGICAL SURVEY	
SUNDRY NOTICES AND REPORTS ON WELLS  (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME  8. FARM OR LEASE NAME
1. oil gas Dry Hole	Federal
well well other	9. WELL NO. 19 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
2. NAME OF OPERATOR  Jerome P. McHugh	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Undesignated 16
P 0 Box 208, Farmington, NM 87401  4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
helow )	Sec 27 T25N R2W
AT SURFACE: 990' FSL - 1650' FWL AT TOP PROD. INTERVAL:	12. COUNTY OR PARISH 13. STATE Rio Arriba NM
AT TOTAL DEPTH:	14. API NO. 3 2 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	TE STATIONS COLONY DE KON AND MON
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF LIFE FRACTURE TREAT	
SHOOT OR ACIDIZE REPAIR WELL	(NOTE: Report results of multiple completion or zone
PULL OR ALTER CASING	change on Form 9-330.)
CHANGE ZONES	
ABANDON*	
(other)	and portional details, and give pertinent dates
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly stat including estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertiner	lifectionally drilled, give subsurface locations and
Plugged and adandoned well as follows:	
••	
<ol> <li>Squeezed perfs 3487-3507 w/ 20 sx cemen</li> <li>Spotted cement plug 3507-3128.</li> </ol>	1022
3. Found csg. free point at 1022. Shot of	f csg. and worked free.
4. Spotted cement plug 50' inside and 50'	on top of 41" csg. stub. 1072 + 972
<ul><li>5. Spotted 34 sx cement plug 212'-100'.</li><li>6. Spotted 50' cement plug in top of surfa</li></ul>	ce csq.
7. Installed dry hole marker and filled pi	ts and restored location.
	ကြည့်ချိုင်းသို့ ခေါ်သည် သို့သည်။ ကြည့်နှစ်သည်။ ကြည့်နှစ်သည်။
· · · · · · · · · · · · · · · · · · ·	
Subsurface Safety Valve: Manu. and Type	<u>Set @ Ft.</u>
18. I hereby certify that the foregoing is true and correct	18/12 OV DPROVED
SIGNED Jim L. Jacobstitle Geologist	DATE 10-13-81APPT AMENDED
(This space for Federal or State of	fice use) AS A
APPROVED BY TITLE	DEC 1 1 1984
CONDITIONS OF APPROVAL, IF ANY:	DEC 1 100  LISTAL BROWN  MILLENBACH  A MANAGER
New contract of the contract o	TAREA MANAGER
TAREA WILL	