## HMITED STATES

DEPARTMENT OF THE INTERIOR  GEOLOGICAL SURVEY		<b>5.</b> LEASE SF 078598		Ŧ.,	e e	
		6. IF INDIAN,	ALLOTTE :	OR TRIBE	NAME	_
SUNDRY NOTICES AND REPORTS ON WE		7. UNIT AGRE Canyon La	_			
eservoir. Use Form 9–331–C for such proposals.)  1. oil gas		8. FARM OR L	EASE NA À	E E	den des	
2. NAME OF OPERATOR  **JERICON *** Bryless**  3. ADDRESS OF OPERATOR		9. WELL NO. 296	महित्व सम्बद्ध सम्बद्ध सम्बद्ध	E :	7 1817 1414 15 (1) 11	
		10. FIELD OR V				- 10
		11. SEC., T., R AREA	., M., OR B	LK. AND	SURVEY	OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 990 FNL ~ 940 FWL AT TOP PROD. INTERVAL:		Sec. 22,	<del>-</del> -			
		12. COUNTY O Rio Arrib		13. STA N.M		_
AT TOTAL DEPTH:  16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF N	NOTICE,	14. API NO.				
REPORT, OR OTHER DATA		15. ELEVATION 6741' GL	VS (SHOV	DF, KDB	AND W	/D)
REQUEST FOR APPROVAL TO:  SUBSEQUENT REPORT  FRACTURE TREAT  SHOOT OR ACIDIZE  SHOOT OR ACIDIZE			to set p	Se plus	rodat fid roda trad	<b>-</b>
REPAIR WELL		Charles 100	results of niu on Form 9-3	Itiple comp	pletion or z	one 
CHANGE ZONES	S. GEOLO	CICAL BURYEY		ne tout a		
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Cle including estimated date of starting any proposed work. If measured and true vertical depths for all markers and zones	early state well is di	all pertinent de	etails, and d, give sub	give pert surface lo	inent dat ocations a	es, and
08-19-80 Plugged by pumping in 100 ft. o by water spacer with 100 ft. su	of Clas	s "B" neat plug. Rele	cement,	follo	wed	
by water spacer with 100 fet 51					Angles of the state of the state of	
			du cana			
<i>(</i> 3)	PR 05	984				
	CON DIST.	DIV.				
Subsurface Safety Valve: Manu. and Type		<b></b>	Set	@	5933 5033	Ft.
18. I mereby certify that the foregoing is true and correct						
SIGNED OPE	erator	DATE	Sep	tember	2, 19	980
The succession for Fordayal	or State offi	re uce) 🗷 🗪		_	- I -	

\*See Instructions on Reverse Side

**NMOCC** 

AREA MANAGER