## STATE OF NEW MEXICO ... ENERGY and MINERALS DEPARTMENT

## OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

## NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operato	or M	ecidian	Oil Inc	Lease	Ticaci	illa	4	Wel. No.	. 7	
Location of Well	n : Unit	Sec. 34	Twp. 25 N	Rge.		5 u	Cou		Acciba	
of Well: Unit Sec. 34 Twp. 25 N				TYPE OF PROD.		METHOD OF PROD. (Flow or Art. Litt)		D.	PROD. MEDIUM	
Upper Completion Pictured Cliffs					Gas		<u> </u>		(Tbg. or Cog.)	
Lower Completion Chacas					Gas		Flour		T1 -	
			PRE-FLC	W SHUT-IN P	RESSURE	DATA	1 16/1/1/		7.62	
Upper Completion	1 0 3	22-93	Length of time shut	idn VA-S	SI press, psig			Stabilized? (Yes or No)		
Lower Completion (g-22-53 Length of time enut-			un )AYS	SI press. paig	St press. paig Stabilized? (Yes or I			(es or No)		
				FLOW TEST	NO. 1					
Confinenced at (hour, date)#  TIME LAPSED TIME PRESSURI				URE	Zone producing (U					
	, date)	SINCE*	Upper Completion	Lower Completion	PROD. 2			REMA	AKS	
6.2	3-93		0	<del></del>			Both	70Y	225	
6.24.93			<del>- 0</del>	0			temporarily			
6-25-93			0	<del>0</del>		aban			/ -(.	
6-21	9-93		<del>D</del> -	0						
6-27	-93		0	0					•	
roductio	on rate di	iring test		•						
)il:		BOPE	based on	Bbls. in	Bbls. in Hours			rav	GOR	
as:				D; Tested thru						
			MID-TES	T SHUT-IN PR	ESSURE I	DATA				
Upper empletion	Joper Hour, date shut-in Length of time shut-in		n	SI press. paig		į.	Stabilized? (Yes or No)			
Lower Hour, date shul-in Length ompletion		Length of time shut-in	th of time shut-in Si		Si press. psig			s or No)		
					·	<del></del>		a # 8 1	v e m	

DEGENVE D JUL 6 1993.

(Continue on reverse side)

OIL CON. DIV.

FLOW TEST NO. 2

ommenced at (hour, da	1(0) 中本		Zone producing (Upper or Lower):					
TIME	LAPSED TIME	PRES	SURE	PROD. ZONE	REMARKS			
(hour, date)	SINCE ##	Upper Completion	Lower Completion	TEMP.				
				1				
		-						
					1			
G25:			FPD: Tested thn		s Grav GOR			
Approved		1993	19	Operator M	est of my knowledge.  POLICE OIL DOC  SUSAN DOLAN  PATRICIA ASSISTANT			
					(W.) 185 (720) 611			
ByOzig	inal Mazad av 18	KM PS SHOLSON	<del></del>	Title	<b>81</b> (9.2) (1981) 2			
DEPU	my <mark>oil</mark> & sas im:	Spector, dist. #?		Date JU	N 3 6 1883			
11116					··			

## NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3 The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shurt-in, in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing , temperatures (gas zones only) and gravity and GOR (oil zones only).