TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL

PULL OR ALTER CASING

MULTIPLE COMPLETE CHANGE ZONES

ABANDON*

ويومون المسترارات

UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

Dec. 1973	Budget Bureau No. 42-R1424		
UNITED STATES	5. LEASE		
DEPARTMENT OF THE INTERIOR	Contract #34 6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
GEOLOGICAL SURVEY			
	Jicarilla Apache		
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME		
reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME		
1. oil gas cher	Jicarilla "C"		
well 🖾 well 🗀 other	9. WELL NO.		
2. NAME OF OPERATOR	30		
Getty Oil Company	10. FIELD OR WILDCAT NAME		
3. ADDRESS OF OPERATOR	Otero-Gallup		
P.O. Box 3360, Casper, Wyoming 82602 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA		
below.)	Section 27-T25N-R5W		
AT SURFACE: 990' FSL & 990' FEL AT TOP PROD. INTERVAL: Same	12. COUNTY OR PARISH 13. STATE		
AT TOTAL DEPTH: Same	Rio Arriba New Mexico		
Danc	14. API NO.		
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	-		
REPORT, ON OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)		
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	6750' GL		
TEST WATER SHUT-OFF			

(NOTE: Report results of multiple completion or zone

change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

U. S. Barreller Harry Barry

SALLMINGTON, N. M.

Spudded @ 11:30 A.M. on 3-25-82.

Set surface casing as follows:

(other) Spud & Set Surface Casing

Hole Size	Casing Size	Wt.#/Ft.	Depth Set	Cementing Information
12 1/4"	8 5/8 "	24#	316'	Cemented with 275 sx of Class "B" cement. Circ. 30 sx of good cement to surface
Subsurface Safety Valve:	Manu. and Type			Set @ Ft.
18. I hereby certify that	the foregoing is true and c	orrect		
SIGNED WWW	TITI	_E <u>Area Superintend</u>	lentoate	3-31-82
	(This sp	ace for Federal or State office	use)	
APPROVED BY	L. IF ANY:	TLE	DATENCE P	TED FOR RECORD

*See Instructions on Reverse Side

FF2 07 1982