

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well ☐ gas ☒ well ☐ other

2. NAME OF OPERATOR

Robert L. Bayless

3. ADDRESS OF OPERATOR

P.O. Box 1541, Farmington, NM 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 810' FSL & 910' FWL

AT TOP PROD. INTERVAL: same

AT TOTAL DEPTH: same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) Spud, cement surface csg. ☐

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐
☐
☐

RECEIVED

APR 13 1982

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

5. LEASE

Contract 42

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Jicarilla

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

AXI "D"

9. WELL NO.

6

10. FIELD OR WILDCAT NAME

Ballard Pic. Cliffs

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 20, T24N, R4W

12. COUNTY OR PARISH

Rio Arriba

13. STATE

N.M.

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

6738' GL

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

04-12-82 Spud at 4:45 p.m. Drilled 97 ft. of 9-5/8" surface hole. Ran 86.5 ft. of 7", 23#/ft., J-55, used casing and set at 97 ft. RKB. Rigged up Woodco Cementers and cemented surface casing with 50 sacks Class "B" cement with 2% CaCl; good circulation throughout job. Circulated 10 sacks cement to the surface. Plug down at 8:00 p.m. on 04-12-82. WOC 8 hrs. Pressure tested cement to 600 psi; held okay.

04-13-82 Drilling at 130 ft.

Subsurface Safety Valve: Manu. and Type _____

Set @ _____

ft.

18. I hereby certify that the foregoing is true and correct

SIGNED _____

Operator

DATE April 13, 1982

(This space for Federal or State office use)

APPROVED BY _____

TITLE _____

DATE _____

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

APR 15 1982

FARMINGTON DISTRICT

BY 645

*See Instructions on Reverse Side

NMOCC