UNITED STATES

UNITED STATES	5. LEASE
DEPARTMENT OF THE INTERIOR	Jicarilla Contract 146
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
GEOLOGICAE SORVE.	Jicarilla Apache
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
to dealer to dell or to deepen or plug back to a different	t SARWOOD LEAGE NAME
Do not use this form for proposals to crimosome the servoir. Use Form 9-331-C for such proposals.)	8. FARM OR LEASE NAME Jicarilla Contract 146
1. oil gas 🔯 atter	9. WELL NO.
well well to other	40
2. NAME OF OPERATOR	, 10. FIELD OR WILDCAT NAME
Amoco Production Company	Lice Mesaverde
3. ADDRESS OF OPERATOR	11. SEC., T., R., M., OR BLK. AND SURVEY OR
501 Airport Drive, Farmington, N.M. 87401 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 1	7 AREA
	SE/SW Section 3, T25N, R5W
AT SURFACE: 1090' FSL X 1030 FWL	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: same	KIO KILIDA
AT TOTAL DEPTH: same	14. API NO. E, 30-039-23159
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTIC	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REPORT, OR OTHER DATA	6648' GL
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	EIVED
FRACTURE TREAT	and the second of the second o
OUGOT OF ACIDITE	NOTE: Report results of multiple completion or zone
REPAIR WHIL	change (sh Form 9-330.)
MULTIPLE COMPLETE	LAND MANAGERA MI RESOURCE AREA
CHANGE ZONES	
ABANDON*	
(other) completion	the details and give pertinent dates.
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly including estimated date of starting any proposed work. If well measured and true vertical depths for all markers and zones pertilioved in and rigged up completion unit 9-8 casing to 4300 PSI. Perforated the follow. 38" in diameter, 5184'-5252', 5276'-5308' diameter for a total of 182 holes. Fraced with 95,000 gals. 20# gelled water and 135 1 millicurie radioactive sand per 1000# sa 5336'. Total depth of the well is 5434' a Released the rig 9-16-83.	s-83. Pressure tested production ging intervals: 5120'-5156' 2 jspf s, 5340'-5350' 1 jspf .38" in d entire interval (5120'-5350') 5,000# 20-40 mesh sand containing and Landed 2.375" tubing at
Subsurface Safety Valve: Manu. and Type 18. Thereby certify that the foregoing is true and correct SIGNED Criginal Signed By TITLE Dist. Adm. (This space for Federal or St.)	Set @ Ft Super. DATE 10-13-83
APPROVED BY TITLE CONDITIONS OF APPROVAL. IF ANY:	MULLIED FOR RECORD
CONDITIONS OF ALL MANNEY	OCT 27 1983
	001 2/ 1303

*See Instructions on Reverse Side

FARMINGIUN RESOURCE AREA BY SMM