

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO.  
30-039-23185

5. Indicate Type of Lease  
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:  
OIL WELL ☐ GAS WELL ☒ OTHER

2. Name of Operator  
Benson-Montin-Greer Drilling Corp.

3. Address of Operator  
4900 College Boulevard, Farmington, NM 87402

4. Well Location  
Unit Letter C : 1100 Feet From The north Line and 1600 Feet From The west Line  
Section 28 Township 25 North Range 2 West NMPM Rio Arriba County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)  
7170' RKB

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐  
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOB ☐  
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Plug #1 To cover perforated zone from 6643' to 7893' (PBTD 7917', TD 8081')  
Will set retainer above top perforation and squeeze perms with 200 sacks cement.  
Will spot 50' cement plug on top of retainer.

Plug #2 To cover Fruitland and Pictured Cliffs formations. 9 c/c  
Set cement plug from 3200' to 3425'.

1600'-1700' 2A  
Neumato Plug #3 To cover surface casing shoe set at 220'.  
Set 100' cement plug from 170' to 270'.

Plug #4 Surface plug.  
Set 50' cement plug from surface to 50' inside 4-1/2" casing.

RECEIVED  
NOV 12 1997  
OIL CON. DIV.  
DIST. 3

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Albert R. Greer TITLE President DATE 11/10/97  
TYPE OR PRINT NAME Albert R. Greer TELEPHONE NO. 325-8874

(This space for State Use)

APPROVED BY Johnny Robinson TITLE DEPUTY OIL & GAS INSPECTOR, DIST. #3 DATE NOV 12 1997  
CONDITIONS OF APPROVAL, IF ANY: As Noted above

NOTIFY AZTEC OCD  
IN TIME TO WITNESS Py A