

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well ☐ gas well ☐ other

2. NAME OF OPERATOR  
Amoco Production Company

3. ADDRESS OF OPERATOR  
501 Airport Drive, Farmington, N.M. 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 330' FSL x 2310' FWL  
AT TOP PROD. INTERVAL: same  
AT TOTAL DEPTH: same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

PULL OR ALTER CASING

MULTIPLE COMPLETE

CHANGE ZONES

ABANDON\*

(other) spud and set casing

SUBSEQUENT REPORT OF:

RECEIVED

OCT 18 1983

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

BUREAU OF LAND MANAGEMENT  
FARMINGTON RESOURCE AREA

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface positions and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Rigged up rotary rig and spudded a 12 1/4" hole on 8-31-83. Drilled to 30' and landed 8.625", 24#, K55 casing at the same depth. Cemented the surface casing with 498 cu ft Class B cement with 2% CaCl<sub>2</sub> and circulated to surface. Pressure tested casing to 800 psi. Reduced hole size to 7 7/8" and reached a TD of 8066' on 9-15-83. Set 5.5", 15.5#, K55 casing at 8066'. Cemented the first stage with 693 cu ft Class B 50:50 POZ cement and tailed in with 148 cu ft Class B neat cement. Circulated to surface. Stage two was cemented with 1872 cu ft Halliburton light cement containing 6% gel. Tailed in with 148 cu ft Class B neat cement. Circulated to the surface. DV tool was set at 6017'. Released the rig 9-18-83.

Subsurface Safety Valve: Manu. and Type

Set

18. I hereby certify that the foregoing is true and correct

SIGNED Original Signed By \_\_\_\_\_ TITLE Dist. Adm. Super. DATE 10-14-83

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

TITLE \_\_\_\_\_ DATE \_\_\_\_\_

ACCEPTED FOR RECORD

OCT 26 1983

\*See Instructions on Reverse Side

FARMINGTON RESOURCE AREA

BY Sm