DISTRIBUTION		P
D13111113011014	7	Form C-103 Supersedes Old
SANTA FE	NEW MEXICO OIL CONSERVATION COMMISSION	C-102 and C-103
FILE	The state of a series of the commission	Effective 1-1-65
U.S.G.S.		5a. Indicate Type of Lease
LAND OFFICE	7	
OPERATOR		5, State Oil & Gas Lease No.
	_	
SIND	DY MOTICES AND DEPORTS ON WELLS	E-1207
(DO NOT USE THIS FORM FOR PR	RY NOTICES AND REPORTS ON WELLS ROPOSALS TO BRILL OR TO BEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. RIGH FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.	
1.	TOTAL CHICITY FOR SUCH PROPOSACS,	
WELL GAS X	OTHER-	7. Unit Agreement Name
2. Name of Operator		
Getty Oil Company	7	8. Farm or Lease Name
). Address of Operator		Farming "E"
P.O. Box 3360 Ca	asper, Wyoming 82602	9. Well No.
Location of Well	isper; "yoming 02002	#3 F
F 1	1160 North 700	10. Field and Pool, or Wildcat
UNIT LETTER	L160 FEET FROM THE NORTH LINE AND 790 FEET FROM	Basin Dakota
West		
THE WEST LINE, SECTI	ION 2 TOWNSHIP 24N RANGE HMP	
mmmmmm	15. Elevation (Show whether DF, RT, GR, etc.)	
		12. County
	6444' GR	Rio Arriba
Check	Appropriate Box To Indicate Nature of Notice, Report or O	ther Data
NOTICE OF I		NT REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON REMEDIAL WORK	ALTERING CASING
TEMPOHARILY ABANDON	COMMENCE DRILLING OPHS.	
PULL OF ALTER CASING	CHANGE PLANS CASING TEST AND CEMENT JOB X a	PLUG AND ABANDONMENT
	OTHER TD and set prod	
THER		
7 Describ Division in Control	perations (Clearly state all pertinent details, and give pertinent dates, including	
7. Describe Proposed of Completed Of	perations (Clearly state all pertinent details, and give pertinent dates, includi-	
WORK) SEE HULE 1103.	· · · · · · · · · · · · · · · · · · ·	ng estimated date of starting any proposed
		ng estimated date of starting any proposed
	0.00	A CONTRACT OF THE PARTY OF THE
Reached TD of 6850'	at 8:00 p.m. on 5-19-84.	A CONTRACT OF THE PARTY OF THE
Reached TD of 6850'	at 8:00 p.m. on 5-19-84. ng as follows:	
Reached TD of 6850'	at 8:00 p.m. on 5-19-84. ng as follows:	
Reached TD of 6850' Ran production casin Hole Size: 7 7/8"	at 8:00 p.m. on 5-19-84. Ing as follows:	1
Reached TD of 6850' Ran production casin Hole Size: 7 7/8" Casing Size: 5 1/2"	at 8:00 p.m. on 5-19-84. Ing as follows:	1
Reached TD of 6850' Ran production casin Hole Size: 7 7/8"	at 8:00 p.m. on 5-19-84. Ing as follows:	1
Reached TD of 6850' Ran production casin Hole Size: 7 7/8" Casing Size: 5 1/2" Depth Set: 6844'	at 8:00 p.m. on 5-19-84. Ing as follows: Cit Cold DIST.	1
Reached TD of 6850' Ran production casin Hole Size: 7 7/8" Casing Size: 5 1/2" Depth Set: 6844' Wt. #/ft & Grade: 1	at 8:00 p.m. on 5-19-84. Ing as follows: CIL CONDIST. 5.5#, 14.0#; K-55	
Reached TD of 6850' Ran production casin Hole Size: 7 7/8" Casing Size: 5 1/2" Depth Set: 6844' Wt. #/ft & Grade: 1 Cementing Informatio	at 8:00 p.m. on 5-19-84. Ing as follows: Cit Colv DIST. 5.5#, 14.0#; K-55 On: RU and cemented first stage with 25 bbls 550	Side Subject 65-35 Page
Reached TD of 6850' Ran production casin Hole Size: 7 7/8" Casing Size: 5 1/2" Depth Set: 6844' Wt. #/ft & Grade: 1 Cementing Informatio cement with 6% gel.	at 8:00 p.m. on 5-19-84. Ing as follows: Cit Cold DIST. 5.5#, 14.0#; K-55 In RU and cemented first stage with 25 bbls 550 10% salt. 6 1/4 #/sk gilsonite and 1/4 #/sk gall	cubic feet 65-35 Poz
Reached TD of 6850' Ran production casin Hole Size: 7 7/8" Casing Size: 5 1/2" Depth Set: 6844' Wt. #/ft & Grade: 1 Cementing Informatio cement with 6% gel, 485 cubic feet Class	at 8:00 p.m. on 5-19-84. Ing as follows: Oil Color DIST. 5.5#, 14.0#; K-55 On: RU and cemented first stage with 25 bbls 550 10% salt, 6 1/4 #/sk gilsonite, and 1/4 #/sk cell B"H" cement with 10% self-stress additive 0.6%	cubic feet 65-35 Poz lophane. Tailed in with
Reached TD of 6850' Ran production casin Hole Size: 7 7/8" Casing Size: 5 1/2" Depth Set: 6844' Wt. #/ft & Grade: 1 Cementing Informatio cement with 6% gel, 485 cubic feet Class 1/4 #/sk cellophane	at 8:00 p.m. on 5-19-84. Ing as follows: CIL DIST. 5.5#, 14.0#; K-55 In: RU and cemented first stage with 25 bbls 550 10% salt, 6 1/4 #/sk gilsonite, and 1/4 #/sk cel "H" cement with 10% self-stress additive, 0.6% flakes. Opened DV tool at 3794'. Circulated on	cubic feet 65-35 Poz lophane. Tailed in with fluid loss additive and
Reached TD of 6850' Ran production casin Hole Size: 7 7/8" Casing Size: 5 1/2" Depth Set: 6844' Wt. #/ft & Grade: 1 Cementing Informatio cement with 6% gel, 485 cubic feet Class 1/4 #/sk cellophane Cemented 2nd stage w	at 8:00 p.m. on 5-19-84. Ing as follows: CIL DIST. 5.5#, 14.0#; K-55 In: RU and cemented first stage with 25 bbls 550 10% salt, 6 1/4 #/sk gilsonite, and 1/4 #/sk cel "H" cement with 10% self-stress additive, 0.6% flakes. Opened DV tool at 3794'. Circulated out with 25 bbl chemical wash. 598 cubic feet of 65-3	cubic feet 65-35 Poz lophane. Tailed in with fluid loss additive and t 20 bbls chemical wash.
Reached TD of 6850' Ran production casin Hole Size: 7 7/8" Casing Size: 5 1/2" Depth Set: 6844' Wt. #/ft & Grade: 1 Cementing Informatio cement with 6% gel, 485 cubic feet Class 1/4 #/sk cellophane Cemented 2nd stage w 10% salt, 6 1/4 #/sk	at 8:00 p.m. on 5-19-84. Ing as follows: CIL DIST. DIST. 5.5#, 14.0#; K-55 In: RU and cemented first stage with 25 bbls 550 10% salt, 6 1/4 #/sk gilsonite, and 1/4 #/sk cel "H" cement with 10% self-stress additive, 0.6% flakes. Opened DV tool at 3794'. Circulated ou with 25 bbl chemical wash, 598 cubic feet of 65-3 gilsonite, and 1/4 #/sk cellophane. Tailed in	cubic feet 65-35 Poz lophane. Tailed in with fluid loss additive and t 20 bbls chemical wash. 5 Poz cement with 6% gel, with 59 cubic feet of
Reached TD of 6850' Ran production casin Hole Size: 7 7/8" Casing Size: 5 1/2" Depth Set: 6844' Wt. #/ft & Grade: 1 Cementing Informatio cement with 6% gel, 485 cubic feet Class 1/4 #/sk cellophane Cemented 2nd stage w 10% salt, 6 1/4 #/sk Class "B" cement with	at 8:00 p.m. on 5-19-84. In as follows: Cit Dist. 5.5#, 14.0#; K-55 In: RU and cemented first stage with 25 bbls 550 10% salt, 6 1/4 #/sk gilsonite, and 1/4 #/sk cel "H" cement with 10% self-stress additive, 0.6% flakes. Opened DV tool at 3794'. Circulated out with 25 bbl chemical wash, 598 cubic feet of 65-3 gilsonite, and 1/4 #/sk cellophane. Tailed in the 2% CaClo. 1/4 #/sk cellophane flakes. Plug do	cubic feet 65-35 Poz lophane. Tailed in with fluid loss additive and t 20 bbls chemical wash. 5 Poz cement with 6% gel, with 59 cubic feet of
Reached TD of 6850' Ran production casin Hole Size: 7 7/8" Casing Size: 5 1/2" Depth Set: 6844' Wt. #/ft & Grade: 1 Cementing Informatio cement with 6% gel, 485 cubic feet Class 1/4 #/sk cellophane Cemented 2nd stage w 10% salt, 6 1/4 #/sk Class "B" cement with DV@ 1812'.Circulated	at 8:00 p.m. on 5-19-84. In as follows: Oliver Dist. 5.5#, 14.0#; K-55 In: RU and cemented first stage with 25 bbls 550 10% salt, 6 1/4 #/sk gilsonite, and 1/4 #/sk cel "H" cement with 10% self-stress additive, 0.6% flakes. Opened DV tool at 3794'. Circulated ou with 25 bbl chemical wash, 598 cubic feet of 65-3 is gilsonite, and 1/4 #/sk cellophane. Tailed in th 2% CaCl ₂ , 1/4 #/sk cellophane flakes. Plug do out 5 bbls good cement at surface. Cemented 3r	cubic feet 65-35 Poz lophane. Tailed in with fluid loss additive and t 20 bbls chemical wash. 5 Poz cement with 6% gel, with 59 cubic feet of wn at 11:45 p.m. Open d stage with 25 bbls
Reached TD of 6850' Ran production casin Hole Size: 7 7/8" Casing Size: 5 1/2" Depth Set: 6844' Wt. #/ft & Grade: 1 Cementing Informatio cement with 6% gel, 485 cubic feet Class 1/4 #/sk cellophane Cemented 2nd stage w 10% salt, 6 1/4 #/sk Class "B" cement with DV@ 1812'.Circulated	at 8:00 p.m. on 5-19-84. In as follows: Oliver Dist. 5.5#, 14.0#; K-55 In: RU and cemented first stage with 25 bbls 550 10% salt, 6 1/4 #/sk gilsonite, and 1/4 #/sk cel "H" cement with 10% self-stress additive, 0.6% flakes. Opened DV tool at 3794'. Circulated ou with 25 bbl chemical wash, 598 cubic feet of 65-3 is gilsonite, and 1/4 #/sk cellophane. Tailed in th 2% CaCl ₂ , 1/4 #/sk cellophane flakes. Plug do out 5 bbls good cement at surface. Cemented 3r	cubic feet 65-35 Poz lophane. Tailed in with fluid loss additive and t 20 bbls chemical wash. 5 Poz cement with 6% gel, with 59 cubic feet of wn at 11:45 p.m. Open d stage with 25 bbls
Reached TD of 6850' Ran production casin Hole Size: 7 7/8" Casing Size: 5 1/2" Depth Set: 6844' Wt. #/ft & Grade: 1 Cementing Informatio cement with 6% gel, 485 cubic feet Class 1/4 #/sk cellophane Cemented 2nd stage w 10% salt, 6 1/4 #/sk Class "B" cement with DV@ 1812'.Circulated chemical wash, 540 cu	at 8:00 p.m. on 5-19-84. Ing as follows: CIL DIST. 5.5#, 14.0#; K-55 In: RU and cemented first stage with 25 bbls 550 10% salt, 6 1/4 #/sk gilsonite, and 1/4 #/sk cel "H" cement with 10% self-stress additive, 0.6% flakes. Opened DV tool at 3794'. Circulated out with 25 bbl chemical wash, 598 cubic feet of 65-3 in gilsonite, and 1/4 #/sk cellophane. Tailed in th 2% CaCl ₂ , 1/4 #/sk cellophane flakes. Plug do to out 5 bbls good cement at surface. Cemented 3r thic feet 65-35 Poz cement with 6% gel, 10% salt,	cubic feet 65-35 Poz lophane. Tailed in with fluid loss additive and t 20 bbls chemical wash. 5 Poz cement with 6% gel, with 59 cubic feet of wn at 11:45 p.m. Open d stage with 25 bbls
Reached TD of 6850' Ran production casin Hole Size: 7 7/8" Casing Size: 5 1/2" Depth Set: 6844' Wt. #/ft & Grade: 1 Cementing Informatio cement with 6% gel, 485 cubic feet Class 1/4 #/sk cellophane Cemented 2nd stage w 10% salt, 6 1/4 #/sk Class "B" cement with DV@ 1812'.Circulated chemical wash, 540 cu	at 8:00 p.m. on 5-19-84. In as follows: Oliver Dist. 5.5#, 14.0#; K-55 In: RU and cemented first stage with 25 bbls 550 10% salt, 6 1/4 #/sk gilsonite, and 1/4 #/sk cel "H" cement with 10% self-stress additive, 0.6% flakes. Opened DV tool at 3794'. Circulated ou with 25 bbl chemical wash, 598 cubic feet of 65-3 is gilsonite, and 1/4 #/sk cellophane. Tailed in th 2% CaCl ₂ , 1/4 #/sk cellophane flakes. Plug do out 5 bbls good cement at surface. Cemented 3r	cubic feet 65-35 Poz lophane. Tailed in with fluid loss additive and t 20 bbls chemical wash. 5 Poz cement with 6% gel, with 59 cubic feet of wn at 11:45 p.m. Open d stage with 25 bbls 6 1/4 #/sk gilsonite
Reached TD of 6850' Ran production casin Hole Size: 7 7/8" Casing Size: 5 1/2" Depth Set: 6844' Wt. #/ft & Grade: 1 Cementing Informatio cement with 6% gel, 485 cubic feet Class 1/4 #/sk cellophane Cemented 2nd stage w 10% salt, 6 1/4 #/sk Class "B" cement with DV@ 1812'.Circulated chemical wash, 540 cu	at 8:00 p.m. on 5-19-84. Ing as follows: CIL DIST. 5.5#, 14.0#; K-55 In: RU and cemented first stage with 25 bbls 550 10% salt, 6 1/4 #/sk gilsonite, and 1/4 #/sk cel "H" cement with 10% self-stress additive, 0.6% flakes. Opened DV tool at 3794'. Circulated out with 25 bbl chemical wash, 598 cubic feet of 65-3 in gilsonite, and 1/4 #/sk cellophane. Tailed in th 2% CaCl ₂ , 1/4 #/sk cellophane flakes. Plug do to out 5 bbls good cement at surface. Cemented 3r thic feet 65-35 Poz cement with 6% gel, 10% salt,	cubic feet 65-35 Poz lophane. Tailed in with fluid loss additive and t 20 bbls chemical wash. 5 Poz cement with 6% gel, with 59 cubic feet of wn at 11:45 p.m. Open d stage with 25 bbls 6 1/4 #/sk gilsonite
Reached TD of 6850' Ran production casin Hole Size: 7 7/8" Casing Size: 5 1/2" Depth Set: 6844' Wt. #/ft & Grade: 1 Cementing Informatio cement with 6% gel, 485 cubic feet Class 1/4 #/sk cellophane Cemented 2nd stage w 10% salt, 6 1/4 #/sk Class "B" cement with DV@ 1812'.Circulated chemical wash, 540 cu	at 8:00 p.m. on 5-19-84. Ing as follows: CIL DIST. 5.5#, 14.0#; K-55 In: RU and cemented first stage with 25 bbls 550 10% salt, 6 1/4 #/sk gilsonite, and 1/4 #/sk cel "H" cement with 10% self-stress additive, 0.6% flakes. Opened DV tool at 3794'. Circulated out with 25 bbl chemical wash, 598 cubic feet of 65-3 gilsonite, and 1/4 #/sk cellophane. Tailed in th 2% CaCl ₂ , 1/4 #/sk cellophane flakes. Plug do cout 5 bbls good cement at surface. Cemented 3r dbic feet 65-35 Poz cement with 6% gel, 10% salt, sebove is true and complete to the best of my knowledge and belief.	cubic feet 65-35 Poz lophane. Tailed in with fluid loss additive and t 20 bbls chemical wash. 5 Poz cement with 6% gel, with 59 cubic feet of wn at 11:45 p.m. Open d stage with 25 bbls 6 1/4 #/sk gilsonite
Reached TD of 6850' Ran production casin Hole Size: 7 7/8" Casing Size: 5 1/2" Depth Set: 6844' Wt. #/ft & Grade: 1 Cementing Informatio cement with 6% gel, 485 cubic feet Class 1/4 #/sk cellophane Cemented 2nd stage w 10% salt, 6 1/4 #/sk Class "B" cement with DV@ 1812'.Circulated chemical wash, 540 cu	at 8:00 p.m. on 5-19-84. Ing as follows: CIL DIST. 5.5#, 14.0#; K-55 In: RU and cemented first stage with 25 bbls 550 10% salt, 6 1/4 #/sk gilsonite, and 1/4 #/sk cel "H" cement with 10% self-stress additive, 0.6% flakes. Opened DV tool at 3794'. Circulated out with 25 bbl chemical wash, 598 cubic feet of 65-3 in gilsonite, and 1/4 #/sk cellophane. Tailed in th 2% CaCl ₂ , 1/4 #/sk cellophane flakes. Plug do to out 5 bbls good cement at surface. Cemented 3r thic feet 65-35 Poz cement with 6% gel, 10% salt,	cubic feet 65-35 Poz lophane. Tailed in with fluid loss additive and t 20 bbls chemical wash. 5 Poz cement with 6% gel, with 59 cubic feet of wn at 11:45 p.m. Open d stage with 25 bbls 6 1/4 #/sk gilsonite
Reached TD of 6850' Ran production casin Hole Size: 7 7/8" Casing Size: 5 1/2" Depth Set: 6844' Wt. #/ft & Grade: 1 Cementing Information cement with 6% gel, 485 cubic feet Class 1/4 #/sk cellophane Cemented 2nd stage w 10% salt, 6 1/4 #/sk Class "B" cement with DV@ 1812'.Circulated chemical wash, 540 cui	at 8:00 p.m. on 5-19-84. Ing as follows: Cit Cit. DIST. 5.5#, 14.0#; K-55 Ing: RU and cemented first stage with 25 bbls 550 10% salt, 6 1/4 #/sk gilsonite, and 1/4 #/sk cel "H" cement with 10% self-stress additive, 0.6% flakes. Opened DV tool at 3794'. Circulated out with 25 bbl chemical wash, 598 cubic feet of 65-3 gilsonite, and 1/4 #/sk cellophane. Tailed in the 2% CaCl ₂ , 1/4 #/sk cellophane flakes. Plug do tout 5 bbls good cement at surface. Cemented 3r above is true and complete to the best of my knowledge and belief.	cubic feet 65-35 Poz lophane. Tailed in with fluid loss additive and t 20 bbls chemical wash. 5 POZ cement with 6% gel, with 59 cubic feet of wn at 11:45 p.m. Open d stage with 25 bbls 6 1/4 #/sk gilsonite (OVER)
Reached TD of 6850' Ran production casin Hole Size: 7 7/8" Casing Size: 5 1/2" Depth Set: 6844' Wt. #/ft & Grade: 1 Cementing Informatio cement with 6% gel, 485 cubic feet Class 1/4 #/sk cellophane Cemented 2nd stage w 10% salt, 6 1/4 #/sk Class "B" cement with DV@ 1812'.Circulated chemical wash, 540 cu	at 8:00 p.m. on 5-19-84. In as follows: CIL COND DIST. 5.5#, 14.0#; K-55 In: RU and cemented first stage with 25 bbls 550 10% salt, 6 1/4 #/sk gilsonite, and 1/4 #/sk cel "H" cement with 10% self-stress additive, 0.6% flakes. Opened DV tool at 3794'. Circulated out th 25 bbl chemical wash, 598 cubic feet of 65-3 In gilsonite, and 1/4 #/sk cellophane. Tailed in the 2% CaCl ₂ , 1/4 #/sk cellophane flakes. Plug do nout 5 bbls good cement at surface. Cemented 3r In above is true and complete to the best of my knowledge and belief. Title Area Superintendent NK T. CHAVEZ	cubic feet 65-35 Poz lophane. Tailed in with fluid loss additive and t 20 bbls chemical wash. 5 POZ cement with 6% gel, with 59 cubic feet of wn at 11:45 p.m. Open d stage with 25 bbls 6 1/4 #/sk gilsonite (OVER)
Reached TD of 6850' Ran production casin Hole Size: 7 7/8" Casing Size: 5 1/2" Depth Set: 6844' Wt. #/ft & Grade: 1 Cementing Information cement with 6% gel, 485 cubic feet Class 1/4 #/sk cellophane Cemented 2nd stage w 10% salt, 6 1/4 #/sk Class "B" cement with DV@ 1812'.Circulated chemical wash, 540 cui	at 8:00 p.m. on 5-19-84. In as follows: CIL CONDIST. 5.5#, 14.0#; K-55 In: RU and cemented first stage with 25 bbls 550 10% salt, 6 1/4 #/sk gilsonite, and 1/4 #/sk cel "H" cement with 10% self-stress additive, 0.6% flakes. Opened DV tool at 3794'. Circulated out with 25 bbl chemical wash, 598 cubic feet of 65-3 gilsonite, and 1/4 #/sk cellophane. Tailed in th 2% CaCl ₂ , 1/4 #/sk cellophane flakes. Plug do cout 5 bbls good cement at surface. Cemented 3r diction feet 65-35 Poz cement with 6% gel, 10% salt, selected is true and complete to the best of my knowledge and belief. Title Area Superintendent NK T. CHAVEZ SUPERVISOR DISTRICT # 5	cubic feet 65-35 Poz lophane. Tailed in with fluid loss additive and t 20 bbls chemical wash. 5 POZ cement with 6% gel, with 59 cubic feet of wn at 11:45 p.m. Open d stage with 25 bbls 6 1/4 #/sk gilsonite

1/4 #/sk cellophane. Tailed in with 59 cubic feet Class "B" cement with 2% CaCl₂ and 1/4 #/sk cellophane. Circulated out 25 bbls chemical wash and a trace of cement. Plug down at 3:00 a.m. on 5-21-84. Released rig at 4:15 a.m.

Currently we are waiting on a replacement rig for completion operations. Casing test will be performed when completion begins.