

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

5a. Indicate Type of Lease
State ☐ Fee ☒
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-	7. Unit Agreement Name
2. Name of Operator MESA GRANDE RESOURCES, INC.	8. Farm or Lease Name BROWN
3. Address of Operator 1200 Philtower Building, Tulsa, Oklahoma 74103	9. Well No. BROWN #1
4. Location of Well UNIT LETTER N 850 FEET FROM THE South LINE AND 1850 FEET FROM West LINE, SECTION 17 TOWNSHIP 25N RANGE 2W NMPM.	10. Field and Pool, or Wildcat Gav. Mancos/Und. Dakota
15. Elevation (Show whether DF, RT, GR, etc.) 7184	12. County Rio Arriba

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Completed Operations:

Spudded 12 1/4" hole at 2:00 P.M. 7/18/84 by LLL Rig #2. Drilled 234' and set 217' of 9-5/8" 36# K-55 surface casing. Cemented with 112 sx. of Class B Cement, 2% KCl and 1/4 lb. D-39. Good return and circulation. Circulated cement to surface (132 cu ft). Plug down at 9:30 P.M.
Nippled up. Tested surface casing and BOP at 1000 PSI. Held ok.

RECEIVED
JUL 30 1984
OIL CON. DIV.
DIST. 2

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Gregory A. Phillips</u> Gregory A. Phillips	TITLE <u>Geochemist</u>	DATE <u>July 27, 1984</u>
APPROVED BY <u>Original Signed by FRANK T. CHAVEZ</u>	TITLE <u>SUPERVISOR DISTRICT # 3</u>	DATE <u>JUL 30 1984</u>