submit 3 copies to:
appropriate
division office

Approved By Conditions of Approval, if any:

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

	n office	BUREAU OF LAND MANAGEMEN submitted in lieu of Form 3160-5	
2-6-97-17	in and representation of the control	Sundry Notices and Reports on Well	
., s. s.		en e	5. Lease Designation or Serial Number NM 230346. If Indian, Allottee or Tribe Name
1. Type of Well			7. If Unit or CA, Agreement Designation
•	Oil		8. Well Name and Number
2. Name of Operator			Twilight Zone #1
D. M. G. Comp. Delling Comp.			9. API Well Number 30-039-23606
3 Ad	Benson-Montin-Greer Drilling Corp dress & Phone Number of Operator	•	10. Field and Pool, or Exploratory Area
			Gavilan Mancos
501 Airport Drive, Suite 221, Farmington, NM 87401 (505) 325-8874			11. County or Parish, State
4. We	ell Location (Unit Letter, Footage, Se 1850' FSL, 1850' FEL, Sec. 12, T24		Rio Arriba, NM
12.	Type of Submission	Type of Action	Cl
	Notice of Intent	XX Abandonment Recompletion	Change of Plans New Construction
	XX Subsequent Report	Plugging Back	Non-Routing Fracture
	Final Abandonment	Casing Repair Altering Casing	Water Shut-off Conversion to Injection
	- Final Avandonment	Other -	Dispose Water
12.	Describe Proposed or Completed	Operations	
	Plug #1: 6769' - 6719	9'	
		769'. Spot 8 sacks plug on top of CIBP.	DEGE STATE
	Plug #2: 5965' - 586:		Market
	•	balanced plug.	JAN 1 0 1937
	Plug #3: 5698' - 5118		
	Spot 69 sacks balanced plug. Plug #4: 3487' - 3065'		JAN 1 0 1997 OUL GOM. DUV.
	<u> </u>	s balanced plug.	DIGI. 3
	Plug #5: 282' - surface	. •	
		Bullhead 108 sacks cement down 5 1/2" o	casing until good returns circulated to
	NOTE: BLM Repre	sentative Al Yepa was on location at all ti	mes.
I here	eby certify that the foregoing is true and	correct.	
Signa	ature Lings	Title Vice-President	Date <u>12/10/96</u>
Print	ed on Typed Name Virgil L. Stoabs		Telephone Number (505) 325-8874
(Thi	s space for Federal or State use)		
•	· / \	1 2	

Twilight Zone #1 Cement Data for P&A Operation 10-14-96

Plug #1: 6769'-6719'

CIBP set @ 6769'. Spot 8 sx plug on top of CIBP.

Plug #2: 5965'-5865'

Spot 17 sx balanced plug.

Plug #3: 5698'-5118'

Spot 69 sx balanced plug.

Plug #4: 3487'-3065'

Spot 51 sx balanced plug.

Plug #5: 282'-Surface

Perf @ 282'. Bullhead 108 sx cement down 5-1/2" casing until good returns

circulated to surface.

Note: BLM Representative on location at all times (Al Yepa

Randy Blackmon
P&A Supervisor
Pin A Wall Samin

Big A Well Service