

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. E291-7	
7. Unit Agreement Name	
8. Farm or Lease Name Salazar	
9. Well No. #8	
10. Field and Pool, or Wildcat Otero Ch./S. Blanco PC	
12. County Rio Arriba	

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)	
1. OIL <input type="checkbox"/> GAS <input checked="" type="checkbox"/> OTHER-	
2. Name of Operator Curtis J. Little	
3. Address of Operator P.O. Box 1258 Farmington, NM 87499	
4. Location of Well UNIT LETTER <u>K</u> <u>1820</u> FEET FROM THE <u>South</u> LINE AND <u>1830</u> FEET FROM THE <u>West</u> LINE, SECTION <u>23</u> TOWNSHIP <u>25N</u> RANGE <u>6W</u> NMPM.	
15. Elevation (Show whether DF, RT, GR, etc.) 6486' GR	

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	
		OTHER <u>Amended</u>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

12-23-84: Schlumberger TD ³⁴⁷⁶3460'. Log tops: Ojo Alamo 1913
Kirtland 2024
Fruitland 2256
Pictured Cliffs 2480
Lewis 2527
Chacra 3308

Ran 89 joints 4½" casing (N80 11.6# 633') K-55 10.5# 2833' totaling 3468'. Set at 3476' KB. PBTB 3459'. Western cemented w/255 sx. 50/50 Poz, 2% gel, 6.25# HiSeal (536 cu.ft.). Cement circulated to surface (50 sx.) Plug down 4:10 P.M. Pressure tested to 2500 psi for 15 minutes; held OK.

RECEIVED
JAN 18 1985
OIL CON. DIV.
DIST. 3

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Curtis J. Little TITLE Operator DATE 1/16/84

APPROVED BY Original Signed by FRANK T. CHAVEZ TITLE SUPERVISOR DISTRICT # 3 DATE JAN 18 1985

CONDITIONS OF APPROVAL, IF ANY: