

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

(Other instructions on reverse side)

DATE: AUGUST 01, 1985

5. LEASE DESIGNATION AND SERIAL NO.  
NM 23032

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

New Horizon

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

\*Gavilan Mancos/G-G-G Dakot

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 2, T24N, R2W, NMPM

12. COUNTY OR PARISH 13. STATE

Rio Arriba

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

JEROME P. McHUGH

3. ADDRESS OF OPERATOR

P O Box 809, Farmington, NM 87499

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)  
At surface

990' FSL - 1850' FEL

RECEIVED

AUG 09 1985

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

7253' GL; 7265' KB

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Spud and surface casing.

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Spudded 12 1/2" hole at 12:30 PM, 8-6-85. Drilled to 259' and ran 6 jts. (246') 9-5/8" O.D., 36#, J-55 csg. Set at 258' and cemented with 135 sx (159 cf) Class B with 2% CaCl<sub>2</sub>. Plug down at 5:30 PM, 8-6-85. Circulated 1 bbl. cement to surface. W.O.C. for 11 hrs. Pressure tested BOP and casing for 30 min. at 800 psi. Held OK.

RECEIVED

AUG 13 1985

OIL CON. DIV.  
DIST. 3

18. I hereby certify that the foregoing is true and correct

SIGNED

James S. Hazen

TITLE

Field Supt.

DATE

8-7-85

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

385

\*See Instructions on Reverse Side

FARMINGTON RESOURCE AREA