UNITED STATES DEPARTMENT OF THE INTERIOR

_	Contract	126	
6.	IF INDIAN, ALLOTTEE	OR TRIBE	NAME

5. LEASE

	CONCIACE 120
6.	IF INDIAN, ALLOTTEE OR TRIBE NAME
	Jicarilla Apache

1	′ 6.	6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
1		Jicarilla Apache		
Γ	7. UNIT AGREEMENT NAME			
l		NA		
Γ	8.	FARM OR LEASE NAME		
L		Apache		
	9.	WELL NO.		
		149		
l	10.	FIELD OR WILDCAT NAME		
L		Lindrith Gallup-Dakota	١	
ľ	11.	SEC., T., R., M., OR BLK. AND SURVEY OR		
		AREA Section 1 T24N R4W		
l	12.	COUNTY OR PARISH 13. STATE		
L		Rio Arriba New Mexico		
	14.	API NO 30-039-23661		
-	15.	ELEVATIONS (SHOW DF, KDB, AND WD)		
L.				

GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME Jicarilla Apache	
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME NA	
• "	8. FARM OR LEASE NAME Apache	
well well other	9. WELL NO.	
2. NAME OF OPERATOR Cotton Petroleum Corporation	149 10. FIELD OR WILDCAT NAME	
3. ADDRESS OF OPERATOR	Lindrith Gallup-Dakota	
3773 Cherry Creek Dr No. #750, Den, CO 80209 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Section 1 T24N R4W	
below.) AT SURFACE: 680' FSL 935' FEL AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	12. COUNTY OR PARISH 13. STATE Rio Arriba New Mexico	
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	14. API NO 30-039-23661 15. ELEVATIONS (SHOW DF, KDB, AND WD)	
CHANGE ZONES	(NOTE: Report results of multiple completion or zone change on Form 9–330.)	
(other) BUREAU OF LAN	D MAISON,	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spud well at 2:30 pm on March 7, 1985 with Azetec Rig 124. Drill 12-1/4" surface hole to 397', run 397' of 8-5/8" 24# ST&C casing, land casing at 396'. Cement with 260 sacks Class B cement + additives. Circulate out.

Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct Division Prod. Mgrate April 17, 1985 (This space for Federal or State office use) DATE CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR REGORD

*See Instructions on Reverse Side

MAY 0 8 1985