1. oil

well XX

below.)

REPAIR WELL

ABANDON\*

2. NAME OF OPERATOR

3. ADDRESS OF OPERATOR

REQUEST FOR APPROVAL TO: **TEST WATER SHUT-OFF** FRACTURE TREAT SHOOT OR ACIDIZE

PULL OR ALTER CASING MULTIPLE COMPLETE **CHANGE ZONES** 

Form Approved.

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)


4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,

1973		Budget	t Bureau No. 42-R1424	
UNITED STATES	5. l	EASE		
DEPARTMENT OF THE INTERIOR		Contract	129	
GEOLOGICAL SURVEY		6. IFINDIAN, ALLOTTEE OR TRIBE NAME Jicarilla Apache		
UNDRY NOTICES AND REPORTS ON WELLS of use this form for proposals to drill or to deepen or plug back to a different	7. (	JNIT AGREEMENT NA NA	ME	
oir. Use Form 9-331-C for such proposals.)	8.	FARM OR LEASE NAM Apache	E	
vell XX well other	9. 1	WELL NO.		
NAME OF OPERATOR		144		
Cotton Petroleum Corporation	10.	FIELD OR WILDCAT N		T.T
ADDRESS OF OPERATOR	00		Gallup-Dakota	
3773 Cherry Creek Drive N., #750, Den, CO 803	471.	SEC., T., R., M., OR B AREA Sec 13 T2	LK. AND SURVEY OR	
OCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	, '	ARLA DEC 13 11	- 121 20111	
pelow.) NT SURFACE: 718' FSL 2035' FEL	12.	COUNTY OR PARISH	13. STATE	
AT TOP PROD. INTERVAL:		Rio Arriba	New Mexico	
AT TOTAL DEPTH:	14.	API NO 30-039-236	563	
CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,				
REPORT, OR OTHER DATA	15.	ELEVATIONS (SHOW 6843' GR	DF, KDB, AND WD)	
JEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	<b></b>		<del></del>	
WATER SHUT-OFF				
TURE TREAT U	,	V = D		
AIR WELL A REC	E (No	TE: Report results of mu	Itiple completion or zone	

BUREAU OF LAND MANAGEMENT FARMINGTON PESOURCE AREA (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spud well on March 30, 1985 with Aztec Rig #124. Drilled 12-1/4" surface hole to 401', ran 401' 8-5/6" 24# K55 ST&C casing. The casing landed at 400' and was cemented with 275 sacks Class B. Circ out.



APR 2 6 1985

		DIST. 3 " · V
Subsurface Safety Valve: Manu. and Type		Set @ Ft.
18. I hereby certify that the foregoing is t	rue and correct	
SIGNED COMP	TITLE Division Prod. Mgr.	TEApril 17, 1985
	(This space for Federal or State office use)	
APPROVED BY	TITLE D	PATE
CONDITIONS OF APPROVAL, IF ANY:		ACCEPTED FOR RECORD

\*See Instructions on Reverse Side

MAY 0 8 1005