Form 3100~5 (November 1983) (Formerly 9-331)	UNITED STATES DEPARTMENT OF THE IN BUREAU OF LAND MANAG	SUBMIT IN TRIPLICATES NTERIOR verse alde) EMENT	Budget Bureau No. 1004-0115 Expires August 31, 1985 5. LEASE DESIGNATION AND SDEIAL NO Jicarilla Contract 148 6 if INDIAN, ALLOTTER OR TRIPE NAME
SUI (Do not use thi	NDRY NOTICES AND REPO	Jicarilla Apache	
OIL CAR	ОТНЕВ		7. UNIT AGREEMBNY HAME
2. NAME OF OPERATOR			8. PARM OR LEAGE NAME
Amoco Produ	ction Co.		Jicarilla Contract 148
3. ADDRESS OF OPERATO	24		9. WELL NO.
501 Airport Drive, Farmington, N M 87401 4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.			34
4. LOCATION OF WELL (See also space 17 be At ourfoce 1870 FNL X	10 W)	RECEIVED MAY 8 9 1985	West Lindrith Gallup-Dakota 11. abc., T., R., M., OR BLK. AND SURVEY OR ARMA
14. PERMIT NO	15 ELEVATIONS (Show white the state of the s		SE/NE Sec 14, T25N,R5W 12. COUPTY OR PARISH 13. STATE Rio Arriba NM
16	Check Appropriate Box To Indi	cate Nature of Notice, Report, or C	Other Data
	NOTICE OF INTENTION TO:		BHT ABPORT OF:
TEST WATER SHUT-		WATER SHUT-OFF	REPAIRING WELL
FRACTURE TREAT	MULTIPLE COMPLETE	SHOOTING OR ACIDIZING	ABANDONMENT"
NUMBER OF ACCUSE	CHANGE PLANS	(Other) Spud and S	et casing X of multiple completion on Well
(Other)		Completion or Recomple	etion Report and Log term.)
proposed work. If	f well is directionally drilled, give subsurts •	pertinent details, and give pertinent dates, ace locations and measured and true vertica	depend for an maintin and some person
Spud a 12-1	/4" hole on 4-12-85 at 094	45 hrs. Drilled to 328' Se	t 8-5/8", 24#, K55
casing at 3	28' and cemented with 325	cu. ft. Class B Portland.	Circulated cement to
surface. P	ressure tested casing to	1000 psi for 30 minutes.	Drilled a 7-7/8" hole

to a TD of 7920' on 4-27-85. Set 5-1/2", 15.5#, K55 casing at 7920'. Stage 1: cemented with 295 cu. ft. Class B Dowell and tailed in with 555 cu. ft. Class B Dowell. Stage 2: cemented with 1711 cu. ft. Class B Dowell. Circulated cement to surface after both stages.

The DV tool was set at 5220' and the rig was released on 4-27-85.

1 hereby certify the to to the table and co	orrect	
SIGNED ODS Naw	111011	DATE 5-22-85
(This space for Federal or State office use)		DACCEPTED FOR RECORD
CONDITIONS OF APPROVAL, IF ANY:		MAY 20 15.

*See Instructions on Reverse Side