STATE OF NEW MEXICO VERGY AND MINERALS DEPARTMENT

Corico SCCCIVES		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
PERATOR	İ	

OIL CONSERVATION DIVISION

Form C-103

SANTA FE			Revised 10-1-78
	SANTA FE, NEW MEXIC	0 87501	Tuesd's and
FILE	•		State Fee X
U.S.G.S.		•	State State Oil & Gas Lease No.
LAND OFFICE	•	•	<u> </u>
OPERATOR			None
SUNDRY NOT	ICES AND DEPORTS ON WELLS		
SUMURT MUT	ICES AND REPORTS ON WELLS	FFERENT RESERVOIR.	
USE "APPLICATION FOR P	ENDIT 2 FORM CHOILE		7. Unit Agreement liame
1L 🔽 6A9 🗍			
TELL MELL OFFICE	R-		8. Farm or Lease Name
ne of Operator			Howard 1
Mallon Oil Company .		<u></u>	9. Well No.
dress of Operator	50 90303		8
2750 Security Life Buildir	ng, Denver, CO 80202		10. Field and Pool, or Wildcat
cation of Well			Basin Dakota-Undes. Gal
н 1650_	FEET FROM THE North LINE A	ND870_ FEET F	TITITITI MOR
THE East LINE, SECTION	Township 25 North	es 2 West N	~~~ {
	15. Elevation (Show whether DF, RT,	(R, etc.)	12. County Rio Arriba
	7511' G.L.		VIO WITTOWN
		Notice Report of	Other Data
Check Approp	oriate Box To Indicate Nature o	chocker, report of	ENT REPORT OF:
NOTICE OF INTENT	ION TO:	2082540	ERT RE. ORT OF
	<u>ا</u>	<u></u>	
ORM REMEDIAL WORK	PLUG AND ABANDON REMEDIA		ALTERING CASING
PORARILY ABANDON	COMMEN	CE DRILLING OPNS.	PLUG AND ABANDONMENT
L—1	CHANGE PLANS CASING	TEST AND CEMENT JOB	_
OR ALTER CASING	OTHE	R	
THER			the state of the s
	Clearly state all pertinent details, and	give pertinent dates, incli	laing estimated date of starting any property
work) SEE RULE 1103.	,		
6-3-85 sp # ud well @ 12:3 48 and 354.5 #/ft	0 p.m. 6/2/85. Drilled 27 casing. Set casing @ 270 Class B with 2% CaCl ₂ . Go to the surface. Plug down	1' of 17½" hole RKB. Cemented	. Ran 258' of 13-3/8" surface casing with
6-3-85 sp 4 ud well @ 12:3 48 and 354.5 #/ft	0 p.m. 6/2/85. Drilled 27 casing. Set casing @ 270	1' of 17½" hole RKB. Cemented	. Ran 258' of 13-3/8" surface casing with
6-3-85 sp 4 ud well @ 12:3 48 and 354.5 #/ft	0 p.m. 6/2/85. Drilled 27 casing. Set casing @ 270	1' of 17½" hole RKB. Cemented	. Ran 258' of 13-3/8" surface casing with
6-3-85 sp # ud well @ 12:3 48 and 354.5 #/ft	0 p.m. 6/2/85. Drilled 27 casing. Set casing @ 270	1' of 17½" hole RKB. Cemented	. Ran 258' of 13-3/8" surface casing with
6-3-85 sp 4 ud well @ 12:3 48 and 354.5 #/ft	0 p.m. 6/2/85. Drilled 27 casing. Set casing @ 270	1' of 17½" hole RKB. Cemented	. Ran 258' of 13-3/8" surface casing with
6-3-85 sp 4 ud well @ 12:3 48 and 354.5 #/ft	0 p.m. 6/2/85. Drilled 27 casing. Set casing @ 270	1' of 17½" hole RKB. Cemented	. Ran 258' of 13-3/8" surface casing with throughout job. 6/2/85. WOC.
6-3-85 sp 1 ud well @ 12:3 48 and 354.5 #/ft	0 p.m. 6/2/85. Drilled 27 casing. Set casing @ 270	1' of 17½" hole RKB. Cemented od circulation on @ 10:00 p.m.	Ran 258' of 13-3/8" surface casing with throughout job. 6/2/85. WOC.
6-3-85 sp 1 ud well @ 12:3 48 and 354.5 #/ft	0 p.m. 6/2/85. Drilled 27 casing. Set casing @ 270	1' of 17½" hole RKB. Cemented od circulation on @ 10:00 p.m.	Ran 258' of 13-3/8" surface casing with throughout job. 6/2/85. WOC.
6-3-85 sp 1 ud well @ 12:3 48 and 354.5 #/ft	0 p.m. 6/2/85. Drilled 27 casing. Set casing @ 270	1' of 17½" hole RKB. Cemented od circulation on @ 10:00 p.m.	Ran 258' of 13-3/8" surface casing with throughout job. 6/2/85. WCC.
6-3-85 sp 1 ud well @ 12:3 48 and 354.5 #/ft	0 p.m. 6/2/85. Drilled 27 casing. Set casing @ 270	1' of 17½" hole RKB. Cemented od circulation on @ 10:00 p.m.	Ran 258' of 13-3/8" surface casing with throughout job. 6/2/85. WCC.
6-3-85 sp 1 ud well @ 12:3 48 and 354.5 #/ft	0 p.m. 6/2/85. Drilled 27 casing. Set casing @ 270	1' of 17½" hole RKB. Cemented od circulation on @ 10:00 p.m.	Ran 258' of 13-3/8" surface casing with throughout job. 6/2/85. WOC.
6-3-85 sp 4 ud well @ 12:3 48 and 354.5 #/ft	0 p.m. 6/2/85. Drilled 27 casing. Set casing @ 270	1' of 17½" hole RKB. Cemented od circulation on @ 10:00 p.m.	Ran 258' of 13-3/8" surface casing with throughout job. 6/2/85. WOC.
6-3-85 sptud well @ 12:3 48 and 354.5 #/ft 330 ft (280 sx) Circulated cement	O p.m. 6/2/85. Drilled 27 casing. Set casing @ 270 Class B with 2% CaCl ₂ . Go to the surface. Plug do	1' of 17½" hole RKB. Cemented od circulation on @ 10:00 p.m.	Ran 258' of 13-3/8" surface casing with throughout job. 6/2/85. WCC.
6-3-85 splud well @ 12:3 48 and 354.5 #/ft 330 ft (280 sx) Circulated cement	O p.m. 6/2/85. Drilled 27 casing. Set casing @ 270 Class B with 2% CaCl ₂ . Go to the surface. Plug do	1' of 17½" hole RKB. Cemented od circulation on @ 10:00 p.m.	Ran 258' of 13-3/8" surface casing with throughout job. 6/2/85. WCC.
48 and 354.5 #/ft	O p.m. 6/2/85. Drilled 27 casing. Set casing @ 270 Class B with 2% CaCl ₂ . Go to the surface. Plug do	1' of 17½" hole RKB. Cemented od circulation on @ 10:00 p.m.	Ran 258' of 13-3/8" surface casing with throughout job. 6/2/85. WOC.
6-3-85 splud well @ 12:3 48 and 354.5 #/ft 330 ft (280 sx) Circulated cement	O p.m. 6/2/85. Drilled 27 casing. Set casing @ 270 Class B with 2% CaCl ₂ . Go to the surface. Plug down to the surface. Plug down to the surface.	1' of 17½" hole RKB. Cemented bod circulation on @ 10:00 p.m.	Ran 258' of 13-3/8" surface casing with throughout job. 6/2/85. WOC.
6-3-85 splud well @ 12:3 48 and 354.5 #/ft 330 ft (280 sx) Circulated cement	O p.m. 6/2/85. Drilled 27 casing. Set casing @ 270 Class B with 2% CaCl ₂ . Go to the surface. Plug down to the surface. Plug down to the surface.	1' of 17½" hole RKB. Cemented od circulation on @ 10:00 p.m.	Ran 258' of 13-3/8" surface casing with throughout job. 6/2/85. WOC.
6-3-85 splud well @ 12:3 48 and 354.5 #/ft 330 ft (280 sx) Circulated cement	O p.m. 6/2/85. Drilled 27 casing. Set casing @ 270 Class B with 2% CaCl ₂ . Go to the surface. Plug down to the surface. Plug down to the surface of my known to the best of m	1' of 17½" hole RKB. Cemented bod circulation on @ 10:00 p.m.	Ran 258' of 13-3/8" surface casing with throughout job. 6/2/85. WOC.
6-3-85 sptud well @ 12:3 48 and 354.5 #/ft 330 ft (280 sx) Circulated cement	O p.m. 6/2/85. Drilled 27 casing. Set casing @ 270 Class B with 2% CaCl ₂ . Go to the surface. Plug down	1' of 17½" hole RKB. Cemented bod circulation on @ 10:00 p.m.	Ran 258' of 13-3/8" surface casing with throughout job. 6/2/85. WOC.