Form 3160-5 (June 1990)

## **UNITED STATES** DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

FORM APPROVED Budget Bureau No. 1004-0135

Expires: March 31, 1993

5. Lease Designation and Serial No. NM 23039

## SUNDRY NOTICES AND REPORTS ON WELLS

| Do not use this form for proposals to de Use "APPLICATION FO  | 6. If Indian, Allottee or Tribe Name   |   |
|---|--|---|
| SUBMIT  | 7. If Unit or CA, Agreement Designation  |   |
| 1. Type of Well    Cas   Well   Gas   Other   2. Name of Operator   Benson-Montin-Greer Drilling   3. Address and Telephone No.   4900 College Blvd., Farmingto   4. Location of Well (Footage, Sec., T., R., M., or Survey Drilling   1650' FNL, 1850' FWL, Sec.   29  | 8. Well Name and No. Full Sail B #3 9. API Well No. 30-039-23853 10. Field and Pool, or Exploratory Area Gavilan Mancos 11. County or Parish, State Rio Arriba, New Mexico   |   |
|   | (s) TO INDICATE NATURE OF NOTICE, REF  |   |
| TYPE OF SUBMISSION  | TYPE OF ACTION   | ON  |
| Notice of Intent  Subsequent Report  Final Abandonment Notice   | Abandonment Recompletion Plugging Back Casing Repair Altering Casing Other   | Change of Plans  New Construction  Non-Routine Fracturing  Water Shut-Off  Conversion to Injection  Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) |
| give subsurface locations and measured and true vertiples are subsurface locations. | all pertinent details, and give pertinent dates, including estimated date of stical depths for all markers and zones pertinent to this work.)*  cated zone from 6783' to 7028'  c 6733' w/ 50' cement plug on top of |   |
| Set letainer at   | . 0733 w/ 30 cement plug on top of   | refarmer  |

|        | Set retainer at 6/33, M/ 30, cement bind ou tob of Le                                     | tainer                   |
|--------|---|--------------------------|
| Plug # | to cover Pictured Cliffs and Fruitland formations<br>Set cement plug form 3295' to 3470'. | DEGEIVED<br>NOV - 7 1997 |
| Plug # | to cover surface casing shoe set at 275' Set 100' cement plug from 225' to 325'.          | @01L GON. DOV.           |
| Plug # | surface plug Set 50' cement plug from surface to 50' inside 5 1/2"                        | DIST, 3                  |

| 14. I hereby certify that the follogoing is too and      | correct | Tide Vice-President                      | Date _ | 0/24/97 |        |
|--|---------|--|--------|---------|--------|
| (This space for Federal/or State office use) Approved by |         | Title Chief, Lands and Mineral Resources | Date   | NOV     | 5 1997 |
| Conditions of approval, if any:                          | Su      | are restriction in attale                | را ال  | ther -  |        |

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

## CONDITIONS OF APPROVAL FOR PERMANENT ABANDONMENT

## Operator BMG Drilling Corp. Well Name Full Sail B #3

- 1. Plugging operations authorized are subject to the "General Requirements for Permanent Abandonment of Wells on Federal Leases."
- 2. For wells on Federal leases, Al Yepa with the Cuba Field Office is to be notified at least 24 hours (48 hours if possible) before the plugging operations commence. His phone number is (505) 289-3748. Office hours are 7:45 a.m. to 4:30 p.m.

For wells on Jicarilla leases notify Erwin Elote with the Jicarilla Apache Tribe at least 24 hours (48 hours if possible) before the plugging operations commence. His phone number is (505) 759-3242.

- 3. Blowout prevention equipment is required.
- 4. The following modifications to your plugging program are to be made:

A plug will be placed from 1400' to 1500' to isolate the Nacimiento.