

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name
2. Name of Operator JEROME P. McHUGH		8. Farm or Lease Name Janet
3. Address of Operator P O Box 809, Farmington, NM 87499		9. Well No. 3
4. Location of Well UNIT LETTER <u>E</u> <u>1850</u> FEET FROM THE <u>North</u> LINE AND <u>990</u> FEET FROM THE <u>West</u> LINE, SECTION <u>21</u> TOWNSHIP <u>25 N</u> RANGE <u>2W</u> NMPM.		10. Field and Pool, or Wildcat G-G-G Gavilan Mancos/Dakota
15. Elevation (Show whether DF, RT, GR, etc.) 7202' GL		12. County Rio Arriba

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Moved in and rigged up Four Corners Drlg. Co. Rig #14.  
Spudded 12½" hole at 11:30 PM 10/16/85.  
Ran 6 jts. 9-5/8", 36#, K-55 casing (243'); set at 255' KB.  
Cemented with 140 sx Class "B" with 2% CaCl<sub>2</sub> (165 cf).  
Circulated 2 bbls. cement to surface. W.O.C. 12 hrs.  
Pressure tested to 600 psi for 30 min. Held OK.

OCT 22 1985

OIL CON. DIV.  
DIST. 3

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED James S. Hazen TITLE Field Supt. DATE 10/18/85

APPROVED BY Original Signed by FRANK T. CHAVEZ TITLE SUPERVISOR DISTRICT #3 DATE OCT 22 1985

CONDITIONS OF APPROVAL, IF ANY: