Form 3160-5 (November 1983) nerly 0

30-039-23914

16

UNITED STATES

SUBMIT IN TRIPLICATES

rorm approved. Budget Bureau No. 1004-0135

Expires August 31, 1985

New Mexico

RTMENT OF THE INTERIOR	verse side)	5. LEASE DESIGNATION AND S
REAU OF LAND MANAGEMENT		NM-04075

BUREA	J OF LAND MANAGEMEN	Τ	NM-04075	
SUNDRY NOT	CES AND REPORTS (talls to drill or to deepen or plug letton FOR PERMIT—" for such p	ON WELLS pack to a different reservoir. roposals.)	8. IF INDIAN, ALLOTTEE	OR TRIBE NAME
OIL X GAS X OTHER			7. UNIT AGREEMENT NAM	
2. NAME OF OPERATOR ARCO Oil and Gas Company	, Division of Atlant	ic Richfield Company	8. FARM OR LEASE NAME C.R. Leeson R	_
3. ADDRESS OF OPERATOR P.O. BOX 5540, Denver, C 4. LOCATION OF WELL (Report location of	olorado 80217 R	ECEIVED	9. WELL NO. ARCO Hill #2	
4. LOCATION OF WELL (Report location of See also space 17 below.) At surface 970' FSL & 99		NOV 29 1985	W. Lindrith/Ga 11. SEC., T., E., M., OR BU SURVEY OR AREA	llup/Dakota
	BUF CO. L. FA	REAU OF LAND MANAGEMENT	22-25N-3W	13. STATE
14. PERMIT NO. 30-039-23914	7335 GL	ry mry day alesy in EGO Office AREA	Rio Arriba	New Mexico

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data SUBSEQUENT REPORT OF: NOTICE OF INTENTION TO: REPAIRING WELL PULL OR ALTER CASING WATER SHUT-OFF TEST WATER SHUT-OFF ALTERING CASING FRACTURE TREATMENT MULTIPLE COMPLETE FRACTURE TREAT ABANDONMENT* SHOOTING OR ACIDIZING SHOOT OF ACIDIZE SPUD REPAIR WELL CHANGE PLANS (Norz: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) (Other)

7335' GL

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and sones pertinent to this work.) *

MI RU Bayless Rig #1. SPUD 12½" hole @0400 hrs 11-22-85. Drilled ahead to 525'. RU and ran 13 jts 9-5/8" 36#, K-55, STC casing and set @ 525'. Cemented with 300 sx Class "B" + 2% CaCl2 + 1/4 sx flocele (yield 1.20 cuft/sx). Good returns. Circl'd 25 bbls cement to surface. $\overline{\text{NU}}$ and pressure tested BOP to 250 psi for 5 mins and 3000 psi for 15 mins held OK. Pressure tested casing to 1000 psi for 15 mins - held OK.

Drilled cement and drilling ahead 11-25-85.

18. I hereby certify that the foregoing is true and cor					-	
SIGNED JMMcCartal /	TITLE Di	istrict	Drilling	Superinten	ent	11-26-85
J.M. McCarthy	4					
(This space for Federal or State office use)					1.15	→ 1.1 m
APPROVED BY	TITLE		,	I	DATE	e e e e e e e e e e e e e e e e e e e

*See Instructions on Reverse Side