STATE OF NEW MEXICO 3 NMOCD 1 DE	l Dugan l File	
DISTRIBUTION P. O. I	VATION DIVISION BOX 2088 EW MEXICO 87501	Form C-103 Revised 19-1-7
U.S.O.S.  LAND OFFICE  OPERATOR		State Oil & Gas Lease No.
SUNDRY NOTICES AND REPORTS ( 100 NOT USE THIS FORM FOR PROPOSALS TO DRILL ON TO DEEPEN OR PLA USE "APPLICATION FOR PERMIT _" (FORM E-101) FOR	ON WELLS JUG BACK TO A DIFFERENT RESERVOIR. SUCH PROPOSALS.	7, Unit Agreement Name
OIL XX GAS WELL OTHER-		8. Form or Lease Name
JEROME P. McHUGH		High Adventure
P O Box 809, Farmington, NM 87499		9. Well No.
WHIT LETTER M . 790 FEET FROM THE SOU	th LINE AND 990 FEET FRO	10. Field and Pool, or Wildcat G-G-G DAKOTA & GAVILAN MANCOS
THE West LINE, SECTION 9 TOWNSHIP 25	N RANGE 2W NMPH	
7315 GL	her DF, RT, GR, etc.)	12. County Rio Arriba
Check Appropriate Box To Indicate NOTICE OF INTENTION TO:	_	ther Data T REPORT OF:
PERFORM REMEDIAL WORK  TEMPORARILY ABANDON  PULL OR ALTER CASING  CHANGE PLANS	REMEDIAL WORK  COMMENCE DRILLING OPHS.  CASING TEST AND CEMENT JQB XX	A TERING CASING PLUG AND ABANDONMENT
OTHER		
17. Describe Proposed or Completed Operations (Clearly state all pertinent of work) SEE RULE 1903.  See attached report of $5\frac{1}{2}$ " casing		
	OCT 02 1986	
	OIL CON. DIV.) DIST. 3	
18. I hereby certify that the information above is true and complete to the bes	t of my knowledge and heliaf	
and Star	Field Supt.	DATE 10/1/86
Original Signed by FRANK T. CHAVEZ	SUPERVISOR DISTRICT <b>驷 3</b>	GAT 02 1986

CONDITIONS OF APPROVAL, IF ANY:

JEROME P. McHUGH High Adventure #2

Reached TD of 8270' KB on 9/28/86.

25 jts. of 5-1/2", L-80, 17#, LT&C csg. (996.17') 157 jts. of 5-1/2", K-55, 17#, LT&C csg. (6346.94') 23 jts. of 5-1/2", L-80, 17#, LT&C csg. (949.62') Ran

Lanced at 8261' KB with Dowell DV tools at 6047' & 3749' KB.

Cemented as follows: 1st stage 10 bbl. mud flush 440 sx 50/50 poz w/ 2% gel, 6-1/4#/sk Kolite & 1/4 #/sk celo flake Plug cown at 8:45 am. Float checked good. (612 cu.ft.)

Plug down at 8:45 am. Float checked good. (61% cu.ft.)
Circulated with rig pump 3 hrs.

10 bbl. mud flush
230 sx 65/35 boz w/ 12% gel & 1/4 #/sk celo flake
200 sx 50/50 boz w/ 2% gel, 6-1/4 #/sk Kolite & 1/4 #/sk celo flake
Plug down at 1:00 bm. Float checked good. (881 cu.ft.)
Circulated with rig pump 2 hrs.

3rd stage

3rd stage
400 sx 65/35 boz w/ 12% gel & 1/4 #/sk celo flake
75 sx 50/50 boz w/ 2% gel, 6-1/4 #/sk Kolite & 1/4 #/sk celo flake
Plug down at 3:50 pm. Float checked good. (115% cu.ft.)

Cemented with full returns throughout job with 2 bbls. of good cement circulated to surface.

Released rig at 5:30 pm 9/30/86.

