

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Benson-Montin-Greer Drilling Corp.

3. Address and Telephone No.

4900 College Blvd., Farmington, NM 87402 (505) 325-8874

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1420' FSL, 660' FEL, Sec. I30, T25N, R2W, NMPM

5. Lease Designation and Serial No.

NM 23039

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Full Sail C #4

9. API Well No.

30-039-24057

10. Field and Pool, or Exploratory Area

Gavilan Mancos

11. County or Parish, State

Rio Arriba, New Mexico

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other _____
- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plug #1 to cover perforated zone from 6774' to 7021'
Set retainer at 6724' w/ 50' cement plug on top of retainer.

Plug #2 to cover Pictured Cliffs and Fruitland formations
Set cement plug from 3265' to 3442'.

Plug #3 to cover surface casing shoe set at 252'
Set 100' cement plug from 202' to 302'.

Plug #4 surface plug
Set 50' cement plug from surface to 50' inside 5 1/2" casing.

RECEIVED
NOV - 7 1997

OIL CON. DIV.
DIST. 3

14. I hereby certify that the foregoing is true and correct

Signed Philip J. Strato

Title Vice-President

Date 10/24/97

(This space for Federal or State office use)

Approved by [Signature]
Conditions of approval, if any:

for Chief, Lands and Mineral Resources

Date NOV 5 1997

Come Nacimiento - Surface restoration in attached letter -

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

CONDITIONS OF APPROVAL FOR PERMANENT ABANDONMENT

Operator BMG Drilling Corp. Well Name Full Sail C #4

1. Plugging operations authorized are subject to the "General Requirements for Permanent Abandonment of Wells on Federal Leases."
2. For wells on Federal leases, Al Yepa with the Cuba Field Office is to be notified at least 24 hours (48 hours if possible) before the plugging operations commence. His phone number is (505) 289-3748. Office hours are 7:45 a.m. to 4:30 p.m.

For wells on Jicarilla leases notify Erwin Elote with the Jicarilla Apache Tribe at least 24 hours (48 hours if possible) before the plugging operations commence. His phone number is (505) 759-3242.

3. Blowout prevention equipment is required.
4. The following modifications to your plugging program are to be made :

A plug will be placed from 1400' to 1500' to isolate the Nacimiento.