

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		5. LEASE DESIGNATION AND SERIAL NO. SF 081334
2. NAME OF OPERATOR Reading & Bates Petroleum Co.		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR 2200 Mid-Continent Tower Tulsa, OK 74103		7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 990'FNL 990'FEL		8. FARM OR LEASE NAME Greenlee Federal
14. PERMIT NO.		9. WELL NO. 41-24
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 7212 GR		10. FIELD AND POOL, OR WILDCAT Gavilan Mancos
		11. SEC., T., E., M., OR BLK. AND SURVEY OR AREA Sec. 24-T25N-R3W
		12. COUNTY OR PARISH Rio Arriba
		13. STATE NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANE

(Other)

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spud 7/25/87 @ 2:00 P.M.

Drilled 12 1/4" surface hole to 511'.

Ran 9-5/8" casing on 7/25/87 as follows:

1 guide shoe	1'
1 jt 9-5/8" K55 36#	44.20'
1 float insert	-
10 jts 9-5/8" K55 36#	446'
	491.20'

Casing cemented @ 503'KB as follows:

350 ft³ Class "B" + 2% CaCl₂ + 1/4# celloseal/sk

Cement circulated to surface.

Tested to 600 psi for 30 min., no pressure loss.

18. I hereby certify that the foregoing is true and correct

SIGNED Matthew C. Frihart

TITLE Sr. Engineer Technician

DATE 9/1/87

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side