

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

07 DEC 11 AM 9:18

2. NAME OF OPERATOR

Benson-Montin-Greer Drilling Corp.

FARMINGTON RESOURCE AREA
FARMINGTON, NEW MEXICO

3. ADDRESS OF OPERATOR

221 Petroleum Center Building, Farmington, NM 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1650' FNL 2310 FWL, Section 7, T25N, R1W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

7442' GR

5. LEASE DESIGNATION AND SERIAL NO.

NM 28701

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Canada Ojitos Unit

8. FARM OR LEASE NAME

Canada Ojitos Unit

9. WELL NO.

38 (F-7)

10. FIELD AND POOL, OR WILDCAT

West Puerto Chiquito Mancos

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Section 7, T25N, R1W

12. COUNTY OR PARISH

Rio Arriba

13. STATE

NM

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☒

SHOOTING OR ACIDIZING ☒

(Other) Perforating report ☒

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

11/20/87

Perforated from 7025' - 7302', 24 settings, two .43" diameter holes each setting.

11/21/87

Acidized with 5000 gallons 15% MSR-100, plus 10 gallons A-250 inhibitor and 10 gallons W-54 non-emulsifying agent.

11/25/87

Sandfraced with 4977 barrels YFOG IV (gelled oil), plus 90,000 pounds 20-40 sand and 88,000 pounds 12-20 sand.

RECEIVED
DEC 17 1987
OIL CON. DIV.
DIST. 3

18. I hereby certify that the foregoing is true and correct

SIGNED

Virgil L. Stoabs

TITLE

Vice President

DATE

12-10-87

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side